




# *Personal Systems Reference Lenovo® ThinkVision® Monitors*

*September 2011 - Version 407*




ThinkVision L2321x Wide Monitor


Visit [www.lenovo.com/psref](http://www.lenovo.com/psref) for the latest version

Name	<b>D186 Wide Flat Panel Monitor</b>	<b>Features</b> <ul style="list-style-type: none"><li>• Widescreen 18.5-inch monitor</li><li>• High Definition (HD) ready; 1366x768 resolution</li><li>• Detachable stand tilts for comfortable viewing</li><li>• Supports VESA mount (100mm)</li><li>• 50% less mercury</li><li>• Kensington® lock slot ready for enhanced security</li></ul>						
Case color	<b>Business black</b>							
Type-model	<b>2580-AB1</b>	 <b>Lenovo D186 Wide Monitor</b>						
Panel	TFT-LCD, twisted nematic (TN), CCFL backlight							
Viewable image size	<b>18.5" (470mm)</b> diagonal							
Max view area (W x H)	16.1" x 9.1" / 409.8mm x 230.4mm							
Optimum resolution	<b>1366x768</b> at 60Hz							
Maximum resolution	1366x768 at 60Hz (135MHz max pixel rate)							
Aspect ratio	16:9							
Pixel pitch (mm)	.300mm							
Dot/Pixel per Inch	85 dpi							
Brightness	200 nits or cd/m² (typical)							
Contrast ratio	600:1 (typical)							
Pixel response time	5ms (typical)							
Color gamut	67%							
Anti-reflective	Anti-reflective, anti-glare							
Viewing angle at 10:1 CR	90° (+/- 45°) horizontal, 50° (+/- 25°) vertical							
Stand	Tilt adjustable stand							
Bezel width	<i>Sides:</i> 0.61" (15.6mm); <i>top:</i> 0.67" (17.1mm); <i>bottom:</i> 1.19" (30.1mm)							
Dimensions (HxWxD)	14.6" H x 17.4" W x 8.3" D; 370mm H x 442mm W x 210mm D							
Power supply	16 watts typical, 24 watts maximum, <1 watts standby/suspend, universal, integrated (no external brick-like power supply)							
Weight	7.28 lb; 3.3kg							
Limited warranty <sup>4</sup>	<b>3 years</b> (includes backlight)							
Available date	January 2010							
VESA-compliant <sup>2</sup>	VESA DDC2B/CI, VESA DPMS-compliant							
Power management	None							
Ergonomics	ISO 9241-307							
Pixel defect	ISO 9241-307 pixel defect standard							
Emission standards	FCC Class B							
Environmental	WEEE, RoHS (EU Directive 2002/95/EC),							
Preset resolutions	VGA: 640x350, 640x480, 720x400 SVGA: 800x600 XGA: 1024x768 WXGA: 1280x720, 1280x768 1360x768, 1366x768							
Presets	Standard presets: 20; user settings: 16							
Viewing adjustments	<i>Tilt:</i> 20° back, -5° forward; no lift; no swivel; detachable stand							
Rotating screen	None							
On screen display	On screen display with digital user controls (8 languages)							
Control features	Direct access (control buttons on front) for automatic image setup and adjustment for brightness							
USB hub	None							
Multiple input	None							
Monitor connectors	VGA 15-pin D-shell, analog, blue							
Signal cables	Detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter							
Mounting features	Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount)							
Security	Security keyhole for attachment of optional cable lock (Kensington lock-compatible)							
Ship group	Monitor, attached stand, Setup poster, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, 1.8 meter analog signal cable, 1.8 meter black power cord							
<b>Limited Warranty</b> <ul style="list-style-type: none"><li>⇒ <b>3 year limited warranty<sup>4</sup></b></li><li>⇒ <b>International Warranty Service<sup>5</sup></b></li><li>⇒ <b>Rapid Replacement Service at 1-800-426-7378</b></li><li>⇒ <b>Replacement normally arrives in two business days, excluding holidays</b></li><li>⇒ <b>Lenovo pays all shipping costs for valid warranty claims<sup>6</sup></b></li><li>⇒ <b>Service upgrade options:<sup>7</sup></b><ul style="list-style-type: none"><li>• <b>3 year, on site exchange, Mon-Fri 9-5 with next day response</b> (ThinkPlus™ part number 41C9209)</li><li>• <b>3 year, on site exchange, 7 day x 24 hr with 4 hour response</b> (41C9212)</li><li>• <b>4 year, on site exchange, Mon-Fri 9-5 with next day response</b> (41C9233)</li><li>• <b>4 year, on site exchange, 7 day x 24 hr with 4 hour response</b> (41C9216)</li><li>• <b>4 year, mail exchange</b> (51J0589)</li><li>• <b>5 year, mail exchange</b> (51J0590)</li></ul></li><li>⇒ <b>24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></b></li></ul>		<b>Accessories</b> <table><tr><td>Kensington MicroSaver® Cable Lock</td><td>73P2582</td></tr><tr><td>Kensington Twin Head Cable Lock</td><td>45K1620</td></tr><tr><td>Lenovo Easy Reach Monitor Stand</td><td>55Y9258</td></tr></table> <p>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a> See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a></p>	Kensington MicroSaver® Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620	Lenovo Easy Reach Monitor Stand	55Y9258
Kensington MicroSaver® Cable Lock	73P2582							
Kensington Twin Head Cable Lock	45K1620							
Lenovo Easy Reach Monitor Stand	55Y9258							

See footnotes for important warranty information  
US model announced January 12, 2010

© Lenovo  
(D186) January 2010

<p>Name <b>L2021 Wide Flat Panel Monitor</b>                  Case color <b>Business black</b>                  Type-model <b>4449-HB1</b>                  Panel <b>TFT-LCD, twisted nematic (TN), CCFL backlight</b>                  Viewable image size <b>20.0" / 508mm</b> (diagonal)                  Max view area (W x H) <b>17.4" x 9.8" / 443mm x 249mm</b>                  Optimum resolution <b>1600x900</b> at 60Hz                  Aspect ratio <b>16:9</b>                  Pixel pitch (mm) <b>0.277mm</b>                  Dot/Pixel per Inch <b>92 dpi</b>                  Brightness <b>250 nits or cd/m<sup>2</sup> (typical)</b>                  Contrast ratio <b>1000:1 (typical)</b>                  Pixel response time <b>5ms (typical)</b>                  Color gamut <b>72%</b>                  Anti-reflective <b>Anti-reflective, anti-glare</b>                  Vertical frequency <b>50 to 75 Hz</b>                  Horizontal frequency <b>31 to 81 kHz</b>                  Viewing angle at 5:1 CR <b>178° (+/- 89°) horizontal, 170° (+/- 85°) vertical</b>                  Viewing angle at 10:1 CR <b>170° (+/- 85°) horizontal, 160° (+/- 80°) vertical</b>                  Stand <b>Tilt adjustable stand</b>                  Bezel width <b>Sides: 0.48" (12.1mm); top: 0.47" (11.9mm); bottom: 0.39" (10.1mm)</b></p> <p>Dimensions (HxWxD) <b>14.1" H x 18.7" W x 5.9" D; 357.5mm H x 475.9mm W x 151.2mm D</b></p> <p>Power supply <b>22 watts typical, 27 watts maximum, &lt;1 watts standby/suspend, universal, integrated (no external brick-like power supply)</b></p> <p>Weight <b>9.24 lb; 4.2kg</b>                  Limited warranty<sup>4</sup> <b>3 years (includes backlight)</b>                  Available date <b>September 2010</b></p>	<p><b>Features</b></p> <ul style="list-style-type: none"> <li>• All-purpose 20-inch wide flat panel LCD monitor</li> <li>• View images in a 16x9 wide aspect ratio</li> <li>• High-bandwidth Digital Content Protection (HDCP)-compliant</li> <li>• Tilt and cable management stand</li> <li>• Compliance with ENERGY STAR 5.0</li> <li>• 50% less mercury</li> <li>• Microsoft® Windows® 7 certified</li> </ul>						
<p>VESA-compliant<sup>2</sup> <b>VESA DDC2B/CI, VESA DPMS-compliant</b>                  Power management <b>ENERGY STAR® 5.0</b>                  Ergonomics <b>ISO 9241-307</b>                  Emission standards <b>MPR-2, FCC Class B</b>                  Environmental <b>EPEAT™ Gold rating, TCO (TCO Displays 5.0), WEEE, RoHS (EU Directive 2002/95/EC)</b></p> <p>Preset resolutions <b>VGA: 640x350, 640x480, 720x400 SVGA: 800x600, 832x624 XGA: 1024x768, 1152x864 WXGA: 1280x720, 1280x768, 1280x800, 1366x768 SXGA: 1280x1024 WXGA+: 1440 x 900, 1600x900</b>                  Presets / user settings <b>Standard presets: 25; user settings: 20</b></p>	<p><b>Lenovo L2021 Wide Monitor</b></p>  <p><b>Lenovo L2021 Wide Monitor rear view with cable management</b></p> 						
<p>Viewing adjustments <b>Tilt: 20° back, -5° forward; detachable stand</b>                  Rotating screen <b>None</b>                  On screen display <b>On screen display with digital user controls (8 languages)</b>                  Control features <b>Direct access (control buttons on front) for automatic image setup</b>                  USB hub <b>None</b>                  Multiple input <b>Multiple input (two different PCs attach to two different connectors; one PC shows image; select via button)</b>                  Monitor connectors <b>(1) VGA 15-pin D-shell, analog, blue (2) Digital Visual Interface (DVI-D) for digital attach [white], <b>HDCP-compliant</b></b>                  Signal cables <b>(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, DVI-D at each end (for digital connector), 1.8 meter</b>                  Mounting features <b>Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (75mm mount)</b>                  Security <b>Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</b></p> <p>Ship group <b>Monitor, attached stand, Setup poster, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, analog signal cable, digital signal cable, 1.8m power cord</b></p>							
<p><b>Limited Warranty</b></p> <p>⇒ <b>3 year limited warranty<sup>4</sup></b>                  ⇒ <b>International Warranty Service<sup>5</sup></b>                  ⇒ <b>Rapid Replacement Service at 1-800-426-7378</b>                  ⇒ <b>Replacement normally arrives in two business days, excluding holidays</b>                  ⇒ <b>Lenovo pays all shipping costs for valid warranty claims<sup>6</sup></b>                  ⇒ <b>Service upgrade options:<sup>7</sup></b></p> <ul style="list-style-type: none"> <li>• <b>3 year, on site exchange, Mon-Fri 9-5 with next day response</b> (ThinkPlus™ part number 41C9209)</li> <li>• <b>3 year, on site exchange, 7 day x 24 hr with 4 hour response</b> (41C9212)</li> <li>• <b>4 year, on site exchange, Mon-Fri 9-5 with next day response</b> (41C9233)</li> <li>• <b>4 year, on site exchange, 7 day x 24 hr with 4 hour response</b> (41C9216)</li> <li>• <b>4 year, mail exchange</b> (51J0589)</li> <li>• <b>5 year, mail exchange</b> (51J0590)</li> </ul> <p>⇒ <b>24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></b></p>	<p><b>Accessories</b></p> <table> <tr> <td>ThinkVision Soundbar</td> <td>45K1263</td> </tr> <tr> <td>Kensington® MicroSaver® Cable Lock</td> <td>73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td>45K1620</td> </tr> </table> <p>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a>                  See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a></p>	ThinkVision Soundbar	45K1263	Kensington® MicroSaver® Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620
ThinkVision Soundbar	45K1263						
Kensington® MicroSaver® Cable Lock	73P2582						
Kensington Twin Head Cable Lock	45K1620						

<p> <b>Name</b> <b>LS2221 Wide Flat Panel Monitor</b>  <b>Case color</b> <b>High gloss black</b>  <b>Type-model</b> <b>5453-LS1</b>  <b>Panel</b> TFT-LCD, twisted nematic (TN), White LED backlight  <b>Viewable image size</b> <b>21.5" (546mm)</b> diagonal  <b>Max view area (W x H)</b> 18.76" x 10.55" (476.6mm x 268.1mm)  <b>Native resolution</b> <b>1920x1080</b>  <b>Aspect ratio</b> 16:9  <b>Pixel pitch (mm)</b> .248mm  <b>Dot/Pixel per Inch</b> 103 dpi  <b>Brightness</b> 250 nits or cd/m<sup>2</sup> (typical)  <b>Contrast ratio</b> 1000:1 (typical)  <b>Dynamic contrast ratio</b> 10000000:1  <b>Pixel response time</b> 5ms (typical)  <b>Color gamut</b> 72%  <b>Viewing angle at 10:1 CR</b> 170° (+/- 85°) horizontal, 160° (+/- 80°) vertical  <b>Stand</b> Tilt adjustable stand  <b>Bezel width</b> Sides: 0.925" (23.5mm)  <b>Dimensions (HxWxD)</b> 15.38" H x 20.67" W x 7.08" D;                      390.7mm H x 525.0mm W x 179.8mm D  <b>Power supply</b> 18 watts typical, 30 watts maximum,                      &lt;1 watts standby/suspend, universal,                      integrated (no external brick-like power supply)  <b>Weight</b> 8.69 lb; 3.95 kg  <b>Limited warranty<sup>4</sup></b> <b>3 year</b> (includes backlight)  <b>Available date</b> August 2011                 </p>	<p><b>Features</b></p> <ul style="list-style-type: none"> <li>• Widescreen 21.5-inch monitor</li> <li>• Supports Full HD 1920x1080 resolution</li> <li>• Ergonomic stand tilts</li> <li>• Includes dual input connection for attachment to two systems concurrently (analog and digital)</li> <li>• Mercury free panel and arsenic free glass</li> <li>• Microsoft® Windows® 7 certified</li> </ul>								
<p> <b>VESA-compliant<sup>2</sup></b> VESA DDC2B/CI, VESA DPMS-compliant  <b>Power management</b> ENERGY STAR® 5.1  <b>Ergonomics</b> ISO 9241-307  <b>Emission standards</b> FCC Class B  <b>Environmental</b> TCO (TCO Displays 5.2), WEEE, RoHS                 </p>	 <p><b>Lenovo LS2221 Wide Monitor</b></p>								
<p> <b>Preset resolutions</b>                     VGA: 640x350, 640x480, 720x400                      SVGA: 800x600, 832x624                      XGA: 1024x768, 1152x864                      SXGA: 1280x1024                      WXGA: 1280x800, 1280x768, 1366x768                      WXGA+: 1440x900, 1600x900                      WSXGA+: 1680x1050                      Full HD: 1920x1080  <b>Presets / user settings</b> Standard presets: 32 (VGA), 32 (DVI);                      user settings: 20                 </p>									
<p> <b>Viewing adjustments</b> Tilt: 20° backward, -5° forward  <b>Rotating screen</b> None  <b>On screen display</b> On screen display with digital user controls (8 languages)  <b>Control features</b> Direct access (buttons on front) for automatic image setup, dual input and NOVO vision  <b>Multiple input</b> Dual input (two different PCs attach to two different connectors; one PC shows image; select via button)  <b>Monitor connectors</b> (1) VGA 15-pin D-shell, analog, blue                      (2) Digital Visual Interface (DVI-D), digital, white, <b>HDCP-compliant</b>  <b>Signal cables</b> (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter                      (2) detachable, DVI-D at each end, digital, 1.8 meter  <b>Mounting features</b> Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount)  <b>Security</b> Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)  <b>Ship group</b> Monitor, attached stand, Setup poster, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, 1.8 meter analog signal cable, 1.8 meter digital signal cable, 1.8 meter black power cord                 </p>									
<p> <b>Limited Warranty</b>                      ➤ <b>3 year limited warranty<sup>4</sup></b>                      ➤ <b>International Warranty Service<sup>5</sup></b>                      ➤ <b>Rapid Replacement Service at 1-800-426-7378</b>                      ➤ <b>Replacement normally arrives in two business days, excluding holidays</b>                      ➤ <b>Lenovo pays all shipping costs for valid warranty claims<sup>6</sup></b>                      ➤ <b>Service upgrade options<sup>7</sup></b> <ul style="list-style-type: none"> <li>• <b>3 year, on site exchange, Mon-Fri 9-5 with next day response</b> (ThinkPlus™ part number 41C9209)</li> <li>• <b>4 year, on site exchange, Mon-Fri 9-5 with next day response</b> (41C9233)</li> <li>• <b>4 year, mail exchange</b> (51J0589)</li> <li>• <b>5 year, mail exchange</b> (51J0590)</li> </ul>                     ➤ <b>24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></b> </p>	<p><b>Accessories</b></p> <table> <tr> <td>Kensington® MicroSaver® Cable Lock</td> <td>73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td>45K1620</td> </tr> <tr> <td>Lenovo Easy Reach Monitor Stand</td> <td>55Y9258</td> </tr> <tr> <td>ThinkCentre Extend Arm</td> <td>57Y4352</td> </tr> </table> <p>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a></p> <p>See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a></p>	Kensington® MicroSaver® Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620	Lenovo Easy Reach Monitor Stand	55Y9258	ThinkCentre Extend Arm	57Y4352
Kensington® MicroSaver® Cable Lock	73P2582								
Kensington Twin Head Cable Lock	45K1620								
Lenovo Easy Reach Monitor Stand	55Y9258								
ThinkCentre Extend Arm	57Y4352								

<div>NameLS2421p Wide Flat Panel Monitor</div> <div>Case colorHigh gloss black</div> <div>Type-model4015-LS1</div> <div>PanelTFT-LCD, twisted nematic (TN), White LED backlight</div> <div>Viewable image size23.6" (598mm) diagonal</div> <div>Max view area (W x H)20.52" x 11.54" (521.3mm x 293.2mm)</div> <div>Native resolution1920x1080</div> <div>Aspect ratio16:9</div> <div>Pixel pitch (mm).272mm</div> <div>Dot/Pixel per Inch93 dpi</div> <div>Brightness300 nits or cd/m² (typical)</div> <div>Contrast ratio1000:1 (typical)</div> <div>Dynamic contrast ratio10000000:1</div> <div>Pixel response time5ms (typical)</div> <div>Color gamut72%</div> <div>Viewing angle at 10:1 CR170° (+/- 85°) horizontal, 160° (+/- 80°) vertical</div> <div>StandTilt adjustable stand</div> <div>Bezel widthSides: 0.968" (24.6mm)</div> <div>Dimensions (HxWxD)13.78" H x 22.44" W x 7.47" D; 350.0mm H x 572.0mm W x 189.8mm D</div> <div>Power supply30 watts typical, 35 watts maximum, &lt;1 watts standby/suspend, universal, integrated (no external brick-like power supply)</div> <div>Weight9.79 lb; 4.44 kg</div> <div>Limited warranty<sup>4</sup>3 year (includes backlight)</div> <div>Available dateAugust 2011</div>	<div><div>Features</div><div><ul style="list-style-type: none"><li>• Widescreen 23.6-inch monitor</li><li>• Supports Full HD 1920x1080 resolution</li><li>• Ergonomic stand tilts</li><li>• Includes dual input connection for attachment to two systems concurrently (analog and digital)</li><li>• Mercury free panel and arsenic free glass</li><li>• Microsoft® Windows® 7 certified</li></ul></div></div>
<div>VESA-compliant<sup>2</sup>VESA DDC2B/CI, VESA DPMS-compliant</div> <div>Power managementENERGY STAR® 5.1</div> <div>ErgonomicsISO 9241-307</div> <div>Emission standardsFCC Class B</div> <div>EnvironmentalTCO (TCO Displays 5.2), WEEE, RoHS</div>	<div></div> <div>Lenovo LS2421p Wide Monitor</div>
<div>Preset resolutions</div> <div>VGA: 640x350, 640x480, 720x400</div> <div>SVGA: 800x600, 832x624</div> <div>XGA: 1024x768, 1152x864</div> <div>SXGA: 1280x1024</div> <div>WXGA: 1280x800, 1280x768, 1366x768</div> <div>WXGA+: 1440x900, 1600x900</div> <div>WSXGA+: 1680x1050</div> <div>Full HD: 1920x1080</div> <div>Presets / user settings</div> <div>Standard presets: 30 (VGA), 27 (HDMI); user settings: 20</div>	
<div>Viewing adjustments</div> <div>Rotating screenNone</div> <div>On screen displayOn screen display with digital user controls (8 languages)</div> <div>Control featuresDirect access (buttons on front) for automatic image setup, dual input, brightness and NOVO vision</div> <div>USB hubUSB 2.0 Hub (1 port into PC, 4 ports for accessories)</div> <div>Multiple inputDual input (two different PCs attach to two different connectors; one PC shows image; select via button)</div> <div>Monitor connectors(1) VGA 15-pin D-shell, analog, blue</div> <div>(2) HDMI (1.3), digital, black, <b>HDCP-compliant</b></div> <div>Signal cables(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter</div> <div>(2) detachable, HDMI at each end, digital, 1.8 meter</div> <div>Mounting featuresWall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount)</div> <div>SecuritySecurity keyhole for attachment of optional cable lock (Kensington® lock-compatible)</div> <div>Ship groupMonitor, attached stand, Setup poster, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, 1.8 meter analog signal cable, 1.8 meter digital signal cable, 1.8 meter black power cord</div>	
<div>Limited Warranty</div> <div><div>➤ 3 year limited warranty<sup>4</sup></div><div>➤ International Warranty Service<sup>5</sup></div><div>➤ Rapid Replacement Service at 1-800-426-7378</div><div>➤ Replacement normally arrives in two business days, excluding holidays</div><div>➤ Lenovo pays all shipping costs for valid warranty claims<sup>6</sup></div><div>➤ Service upgrade options:<sup>7</sup><div><div>• 3 year, on site exchange, Mon-Fri 9-5 with next day response (ThinkPlus™ part number 41C9209)</div><div>• 4 year, on site exchange, Mon-Fri 9-5 with next day response (41C9233)</div><div>• 4 year, mail exchange (51J0589)</div><div>• 5 year, mail exchange (51J0590)</div></div></div><div>➤ 24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></div></div>	<div><div>Accessories</div><div><div><div>Kensington® MicroSaver® Cable Lock</div><div>73P2582</div></div><div><div>Kensington Twin Head Cable Lock</div><div>45K1620</div></div><div><div>Lenovo Easy Reach Monitor Stand</div><div>55Y9258</div></div><div><div>ThinkCentre Extend Arm</div><div>57Y4352</div></div></div><div>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a></div><div>See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a></div></div>



Name	L2461x Wide Flat Panel Monitor		<b>Features</b> <ul style="list-style-type: none"><li>• Widescreen 23.6-inch monitor with white LED backlight</li><li>• 1080p full HD support, HDCP-compliant</li><li>• Full screen multi-touch designed for Windows® 7</li><li>• Supports 120Hz MEMC technology (Motion Estimation, Motion Compensation)</li><li>• 10-60 degree easily adjustable stand and VESA mount</li><li>• Integrated camera (2.0 megapixel) and microphone</li><li>• Light bar supports up to 256-color background light</li><li>• Mercury free panel</li><li>• Easy navigation capacitive touch buttons</li><li>• Microsoft® Windows 7 certified</li></ul>
Case color	High gloss black with metal gray		
Type-model	2467-HE1   4015-HB1		
Panel	TFT-LCD, twisted nematic (TN), white LED backlight supports multi-touch fuction		
Viewable image size	23.6" (599mm) diagonal		
Max view area (W x H)	20.5" x 11.5" / 521.3mm x 293.2mm		
Optimum resolution	1920x1080		
Aspect ratio	16:9		
Pixel pitch (mm)	.272mm		
Dot/Pixel per Inch	93 dpi		
Brightness	300 nits or cd/m² (typical)		
Contrast ratio	1000:1 (typical)		
Pixel response time	5ms (typical)		
Display enhancement	120 Hz MEMC (double frame tech), MPRT<10ms		
Color gamut	68%		
Anti-reflective	Anti-reflective, anti-glare		
Vertical frequency	50 to 75Hz		
Horizontal frequency	30 to 83kHz		
Viewing angle at 10:1 CR	170° (+/- 85°) horizontal, 160° (+/- 80°) vertical		
Stand	Tilt adjustable stand		
Bezel width	Sides: 0.80" (20.4mm)		
Dimensions (HxWxD)	16.69" H x 22.40" W x 6.57" D; 423.8mm H x 569.0mm W x 167.0mm D		
Power supply	27 watts typical, 65 watts maximum, <1 watts standby/suspend, universal, external power adapter with attached 1.8 m DC cord 17.9 lb; 8.1kg		
Weight	1 year		
Limited warranty <sup>4</sup>	(includes backlight)	3 year (includes backlight)	
Available date	March 2010		
VESA-compliant <sup>2</sup>	VESA DDC2B/CI, VESA DPMS-compliant		
Power management	ENERGY STAR <sup>®</sup> 5.0		
Ergonomics	ISO 9241-307		
Emission standards	MPR-2, FCC Class B		
Environmental	TCO Displays 5.0, WEEE, RoHS		
Preset resolutions	VGA: 640x350, 640x480 SVGA: 800x600, 832x624 XGA: 1024x768, 1152x864 SXGA: 1280x1024 WXGA: 1366x768 WXGA+: 1440x900 WSXGA+: 1680x1050 WUXGA: 1920x1080		
Presets / user settings	Presets: 26 (VGA), 24 (HDMI); user settings: 20		
Viewing adjustments	Tilt: 10°-60° back, 0° forward; adjustable stand		
Rotating screen	None		
On screen display	On screen display with digital user controls (8 languages)		
Control features	Direct access (touch-sensitive buttons on front) for Windows shortcuts, speaker volume control, light bar adjustment, and monitor OSD controls		
USB hub	USB 2.0 Hub (1 port into PC, 4 ports for accessories)		
Multimedia	Integrated speakers (Bass Enhanced, 3 watts x 2), 3.5mm Headset audio out		
Camera module	Integrated camera (2.0 megapixel) and dual array microphone		
Light bar	Background light up to 256 colors, light bar adjustment via touch-sensitive button		
Multiple input	Dual input (two different PCs attach to two different connectors; one PC shows image; select via touch-sensitive button)		
Monitor connectors	(1) VGA 15-pin D-shell, analog, blue (2) HDMI (1.3), digital, black, <b>HDCP-compliant</b>		
Signal cables	(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, HDMI at each end, digital, 1.8 meter		
Mounting features	Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI <sup>®</sup> (100mm mount)		
Security	Security keyhole for attachment of optional cable lock (Kensington <sup>®</sup> lock-compatible)		
Ship group	Monitor, attached stand, cable cover, power adapter (1.8 meter DC cord + 1.0 meter power cord), Setup poster, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, 1.8 meter analog signal cable, 1.8 meter HDMI cable, 1.8 meter USB cable, 1.8 meter audio cable		
<div><div><div>Limited Warranty</div><div>⇒ 2467: 1 year limited warranty<sup>4</sup> Rapid Replacement Service at 1-877-453-6686</div><div>⇒ 4015: 3 year limited warranty International Warranty Service<sup>5</sup> Rapid Replacement Service at 1-800-426-7378</div><div>⇒ Replacement normally arrives in two business days, excluding holidays</div><div>⇒ Lenovo pays all shipping costs for valid warranty claims<sup>6</sup></div><div>⇒ 24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></div></div><div><div>Accessories</div><div><div>Kensington MicroSaver<sup>®</sup> Cable Lock73P2582</div><div>Kensington Twin Head Cable Lock45K1620</div><div>Lenovo Easy Reach Monitor Stand55Y9258</div></div><div>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a></div><div>See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a></div></div></div>			

See footnotes for important warranty information  
 US models announced January 5 or March 9, 2010

© Lenovo  
 (L2461X) March 2010

<p> <b>Name</b> LT1421 Wide Mobile Monitor  <b>Case color</b> Raven black  <b>Type-model</b> 1452-DS6 (with Protective Cover)  <b>Panel</b> TFT-LCD, twisted nematic (TN), White LED backlight  <b>Viewable image size</b> 14.0" (355.6mm) diagonal  <b>Max view area (W x H)</b> 12.2" x 6.9" (310.8mm x 175.3mm)  <b>Optimum resolution</b> 1366x768  <b>Aspect ratio</b> 16:9  <b>Pixel pitch (mm)</b> .227mm  <b>Dot/Pixel per Inch</b> 112 dpi  <b>Brightness</b> 200 nits or cd/m<sup>2</sup> (typical)  <b>Contrast ratio</b> 400:1 (typical)  <b>Pixel response time</b> 8ms (typical)  <b>Color gamut</b> 45%  <b>Viewing angle at 10:1 CR</b> 90° (+/- 45°) horizontal, 50° (+/- 25°) vertical  <b>Stand</b> Tilt adjustable stand  <b>Bezel width</b> Sides: 0.476" (12.1mm)  <b>Dimensions (HxWxD)</b> 8.58" H x 13.19" W x 0.37-0.85" D;                      217.9mm H x 335mm W x 9.3-21.5mm D  <b>Power supply</b> 4.2 watts typical, 5 watts maximum,                      &lt;0.1 watts standby/suspend, universal,                      USB 2.0 cable (no external brick-like power supply)  <b>Weight</b> monitor only: 1.8 lb; 0.84 kg;                      with Protective Cover: 2.25 lb; 1.02 kg  <b>Limited warranty<sup>4</sup></b> 3 year (includes backlight)  <b>Available date</b> September 2011                 </p>	<p><b>Features</b></p> <ul style="list-style-type: none"> <li>• Widescreen 14-inch mobile monitor designed for ThinkPad</li> <li>• Light and Slim</li> <li>• Super low power (&lt;5 watts)</li> <li>• Supports 1366x768 resolution</li> <li>• Ergonomic stand tilts, provides a 12° - 40° backward tilt adjustment for comfortable viewing</li> <li>• Detachable USB cable for power and signal</li> <li>• Microsoft® Windows® 7 certified</li> </ul> <div data-bbox="946 443 1503 716"> </div> <p><b>ThinkVision LT1421 Wide Mobile Monitor</b></p>				
<p> <b>VESA-compliant<sup>2</sup></b> VESA DDC2B/CI, VESA DPMS-compliant  <b>Power management</b> ENERGY STAR<sup>®3</sup> 5.1  <b>Emission standards</b> FCC Class B  <b>Environmental</b> WEEE, RoHS  <b>Preset resolutions</b> Display mode and resolution auto setup                 </p>					
<p> <b>Protective Cover</b> Polycarbonate Snap-On Cover protects the LCD Screen while not in use                 </p>	<div data-bbox="1011 804 1438 1031"> </div> <p><b>ThinkVision LT1421 Wide Mobile Monitor with ThinkPad Edge E420s</b></p>				
<p> <b>Viewing adjustments</b> Tilt: 12° - 40° backward  <b>Screen control</b> Brightness (16 levels)  <b>Input</b> USB input  <b>Monitor connectors</b> USB 2.0  <b>Signal cables</b> detachable, USB Y-Type cable, 1.8 meter  <b>Mounting features</b> None  <b>Security</b> Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)                 </p>					
<p> <b>Ship group</b> Monitor, attached tile stand that cannot be removed, Setup poster, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, 1.8 meter USB Y-Type cable, Protective Cover                 </p>					
<p><b>Limited Warranty</b></p> <ul style="list-style-type: none"> <li>⇒ 3 year limited warranty<sup>4</sup></li> <li>⇒ International Warranty Service<sup>5</sup></li> <li>⇒ Rapid Replacement Service at 1-800-426-7378</li> <li>⇒ Replacement normally arrives in two business days, excluding holidays</li> <li>⇒ Lenovo pays all shipping costs for valid warranty claims<sup>6</sup></li> <li>⇒ Service upgrade options:<sup>7</sup> <ul style="list-style-type: none"> <li>• 3 year, on site exchange, Mon-Fri 9-5 with next day response (ThinkPlus™ part number 41C9209)</li> <li>• 4 year, on site exchange, Mon-Fri 9-5 with next day response (41C9233)</li> <li>• 4 year, mail exchange (51J0589)</li> <li>• 5 year, mail exchange (51J0590)</li> </ul> </li> <li>⇒ 24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></li> </ul>	<p><b>Accessories</b></p> <table> <tr> <td>Kensington® MicroSaver® Cable Lock</td> <td>73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td>45K1620</td> </tr> </table> <p>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a></p> <p>See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a></p>	Kensington® MicroSaver® Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620
Kensington® MicroSaver® Cable Lock	73P2582				
Kensington Twin Head Cable Lock	45K1620				

<div>NameL1711p Flat Panel Monitor</div> <div>Case colorBusiness black</div> <div>Type-model5047-HB2</div> <div>PanelTFT-LCD, twisted nematic (TN), CCFL backlight</div> <div>Viewable image size17.0" (432mm) diagonal</div> <div>Max view area (W x H)13.3" x 10.6" (337.9mm x 270.3mm)</div> <div>Optimum resolution1280x1024 at 60Hz</div> <div>Maximum resolution1280x1024 at 75Hz (165MHz max pixel rate)</div> <div>Aspect ratio5:4</div> <div>Pixel pitch (mm)0.264mm</div> <div>Dot/Pixel per Inch96 dpi</div> <div>Brightness250 nits or cd/m² (typical)</div> <div>Contrast ratio1000:1 (typical)</div> <div>Pixel response time5ms (typical)</div> <div>Color gamut72%</div> <div>Anti-reflectiveAnti-reflective, anti-glare</div> <div>Vertical frequency50 to 75Hz</div> <div>Horizontal frequency30 to 83kHz</div> <div>Viewing angle at 10:1 CR160° (+/- 80°) horizontal, 160° (+/- 80°) vertical</div> <div>StandTilt height adjustable stand</div> <div>Bezel widthSides: 0.6" (15.3mm); top: 0.72" (18.4mm); bottom: 1.11" (28.1mm)</div> <div>Dimensions (HxWxD)16-20.33" H x 14.6" W x 6.1" D; 405.7-515.7mm H x 370mm W x 155.2mm D</div> <div>Power supply18 watts typical, 21 watts maximum, &lt;1 watts standby/suspend, universal, integrated (no external brick-like power supply)</div> <div>Weight9.3 lb; 4.21kg</div> <div>Limited warranty<sup>4</sup>3 year (includes backlight)</div> <div>Available dateNovember 2009</div>		<div>Features</div> <div><ul style="list-style-type: none"><li>• Regular screen 17-inch monitor</li><li>• Supports SXGA 1280x1024 resolution</li><li>• Ergonomic stand tilts and provides a 4.3" (110mm) range height adjustment for comfortable viewing</li><li>• Includes dual input connection for attachment to two systems concurrently (analog and digital)</li><li>• Reduces mercury content by 50% and arsenic free glass</li><li>• Up to 70% recycled packaging materials</li><li>• Privacy Filter Slot</li><li>• Microsoft® Windows® 7 certified</li></ul></div>								
<div>VESA-compliant<sup>2</sup>VESA DDC2B/CI, VESA DPMS-compliant</div> <div>Power managementENERGY STAR® 5.0</div> <div>ErgonomicsISO 9241-307</div> <div>Emission standardsMPR-2, MPR-3A, FCC Class B</div> <div>EnvironmentalTCO (TCO Displays 5.0), WEEE, RoHS, EPEAT™ Gold rating</div>		<div></div> <div>ThinkVision L1711p Monitor</div>								
<div>Preset resolutionsVGA: 640x350, 640x480, 720x400</div> <div>SVGA: 800x600</div> <div>XGA: 1024x768</div> <div>SXGA: 1280x1024</div> <div>Presets / user settingsStandard presets: 17; user settings: 22</div>										
<div>Viewing adjustmentsTilt: 20° back, -3° forward; lift: 4.3" (110mm); detachable stand</div> <div>Rotating screenNone</div> <div>On screen displayOn screen display with digital user controls (8 languages)</div> <div>Control featuresDirect access (buttons on front) for automatic image setup</div> <div>Multiple inputDual input (two different PCs attach to two different connectors; one PC shows image; select via button)</div> <div>Monitor connectors(1) VGA 15-pin D-shell, analog, blue</div> <div>(2) Digital Visual Interface (DVI-D), digital, white, <b>HDCP-compliant</b></div> <div>Signal cables(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter</div> <div>(2) detachable, DVI-D at each end, digital, 1.8 meter</div> <div>Mounting featuresWall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount)</div> <div>SecuritySecurity keyhole for attachment of optional cable lock (Kensington® lock-compatible)</div>										
<div>Ship groupMonitor, attached stand, Setup poster, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, 1.8 meter analog signal cable, 1.8 meter digital signal cable, 1.8 meter black power cord</div>										
<div>Limited Warranty</div> <div><ul style="list-style-type: none"><li>⇒ 3 year limited warranty<sup>4</sup></li><li>⇒ International Warranty Service<sup>5</sup></li><li>⇒ Rapid Replacement Service at 1-800-426-7378</li><li>⇒ Replacement normally arrives in two business days, excluding holidays</li><li>⇒ Lenovo pays all shipping costs for valid warranty claims<sup>6</sup></li><li>⇒ Service upgrade options:<sup>7</sup><ul style="list-style-type: none"><li>• 3 year, on site exchange, Mon-Fri 9-5 with next day response (ThinkPlus™ part number 41C9209)</li><li>• 3 year, on site exchange, 7 day x 24 hr with 4 hour response (41C9212)</li><li>• 4 year, on site exchange, Mon-Fri 9-5 with next day response (41C9215)</li><li>• 4 year, on site exchange, 7 day x 24 hr with 4 hour response (41C9216)</li><li>• 4 year, mail exchange (51J0589)</li><li>• 5 year, mail exchange (51J0590)</li></ul></li><li>⇒ 24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></li></ul></div>		<div>Accessories</div> <div><table><tr><td>ThinkVision Soundbar</td><td>45K1263</td></tr><tr><td>Kensington® MicroSaver® Cable Lock</td><td>73P2582</td></tr><tr><td>Kensington Twin Head Cable Lock</td><td>45K1620</td></tr><tr><td>Lenovo Easy Reach Monitor Stand</td><td>55Y9258</td></tr></table></div> <div>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a></div> <div>See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a></div>	ThinkVision Soundbar	45K1263	Kensington® MicroSaver® Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620	Lenovo Easy Reach Monitor Stand	55Y9258
ThinkVision Soundbar	45K1263									
Kensington® MicroSaver® Cable Lock	73P2582									
Kensington Twin Head Cable Lock	45K1620									
Lenovo Easy Reach Monitor Stand	55Y9258									

See footnotes for important warranty information  
US model announced October 20, 2009

© Lenovo  
(L1711P) October 2009



Flat Panel Monitors - US model		Features
Name Case color Type-model Stand Screen Viewable image size (diag) Aspect ratio Pixel pitch (mm) Max view area (inches) Max view area (mm) Viewing angle at 5:1 CR Viewing angle at 10:1 CR Video input Dual input  Rotating screen USB Hub  Optimum resolution Maximum resolution Vertical frequency Horizontal frequency Preset display modes  Presets / user settings Brightness Contrast ratio Pixel response time Color gamut	<b>L197 Wide Flat Panel Monitor</b> <b>Business black</b> <b>4434-HE1</b> Tilt stand LCD Active Matrix TFT (Thin Film Transistor) <b>19.0" / 481mm</b> (diagonal) 16:10 .285mm 16.1" x 10.0" (horizontal x vertical) 408mm x 255mm (horizontal x vertical) 176° vertical, 176° horizontal 160° vertical, 170° horizontal <b>Digital or analog (two separate connectors)</b> <b>Dual input</b> (two different PCs attach to two different connectors; one PC shows image; select via button) No pivot None  <b>1440x900</b> at 60Hz 1440x900 at 75Hz (137MHz maximum pixel rate) 50 to 76Hz 30 to 81kHz VGA: 640x480 60, 66, 72, 75Hz 640x350 70Hz 720x400 70Hz SVGA: 800x600 56, 60, 72, 75Hz 832x624 75Hz XGA: 1024x768 60, 70, 75Hz 1152x864 75Hz SXGA: 1280x1024 60, 70, 75Hz WXGA+: 1440x900 60, 75Hz Standard presets: 20; user settings: 20 250 nits or cd/m <sup>2</sup> (typical) 1000:1 (typical) 5ms (typical) 72%	<ul style="list-style-type: none"> <li>• Widescreen 19-inch flat panel monitor</li> <li>• EPEAT™ Gold rating</li> <li>• View images in a 16:10 wide aspect ratio</li> <li>• Resolution of 1440x900 provides crisp screen images</li> <li>• Slim 14.3mm (0.56") side bezel</li> <li>• High-bandwidth Digital Content Protection (HDCP)-compliant</li> <li>• Includes dual input connection for attachment to two systems concurrently (analog and digital)</li> <li>• Complements the ThinkCentre® and ThinkPad® systems</li> <li>• Microsoft® Windows® Vista™ Premium certified</li> </ul>
		<b>Lenovo ThinkVision L197 Wide</b>
On screen display Control features Monitor connectors  Signal cables  Anti-reflective Dimensions Weight Viewing adjustments Mounting features Security	On screen display with digital user controls (7 languages) Direct access (buttons on front) for automatic image setup Two connectors: (1) analog VGA 15-pin D-shell [blue], (2) Digital Visual Interface (DVI-D) for digital (not analog) attach [white], <b>HDCP-compliant</b> Two cables: (1) detachable, VGA 15-pin D-shell at each end (for analog connector), 1.8 meter, matches color of monitor (2) detachable digital, DVI-D at each end (for digital connector), 1.8 meter, matches color of monitor  Anti-reflective, anti-glare 15.0"H x 17.3"W x 7.0"D / 381mm height x 440mm width x 179mm depth 9.15lb / 4.15kg Tilt: 30° back, 4° forward / no lift, no swivel, detachable stand Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount) Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)	
VESA-compliant <sup>2</sup> Power management Ergonomics Pixel defect Emission standards Environmental Ship group  Power supply Limited warranty <sup>4</sup> Available date	VESA DDC2B/CI, VESA DPMS-compliant ENERGY STAR® 5.0 ISO 13406 Part 2 <sup>1</sup> ISO 13406-2 Class II pixel defect standard MPR-2, MPR-3A, FCC Class B TCO 03, WEEE, RoHS (EU Directive 2002/95/EC), <b>EPEAT™ Gold rating</b> Monitor, attached stand, Setup Guide, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, analog signal cable, digital signal cable, 1.8m black power cord 90-264Vac (universal), integrated (no external brick-like power supply), 22 watts typical, <2 watts standby/suspend <b>3 year</b> (includes backlight) April 2008	
<b>Limited Warranty</b>		<b>Accessories</b>
➤ <b>3 year limited warranty<sup>4</sup></b> ➤ <b>International Warranty Service<sup>5</sup></b> ➤ <b>Rapid Replacement Service at 1-800-426-7378</b> ➤ <b>Replacement normally arrives in two business days, excluding holidays</b> ➤ <b>Lenovo pays all shipping costs for valid warranty claims<sup>6</sup></b> ➤ <b>Service upgrade options:<sup>7</sup></b> <ul style="list-style-type: none"> <li>• <b>3 year, on site exchange, Mon-Fri 9-5 with next day response</b> (ThinkPlus™ part number 41C9209)</li> <li>• <b>3 year, on site exchange, 7 day x 24 hr with 4 hour response</b> (41C9212)</li> <li>• <b>4 year, on site exchange, Mon-Fri 9-5 with next day response</b> (41C9233)</li> <li>• <b>4 year, on site exchange, 7 day x 24 hr with 4 hour response</b> (41C9216)</li> <li>• <b>4 year, mail exchange</b> (51J0589)</li> <li>• <b>5 year, mail exchange</b> (51J0590)</li> </ul> ➤ <b>24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></b>		ThinkVision® USB Soundbar 40Y7616 Kensington® MicroSaver® Cable Lock 73P2582 Kensington Twin Head Cable Lock 45K1620 Lenovo Easy Reach Monitor Stand 55Y9258  See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a>  See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a>

<div>Name</div> <div>Case color</div> <div>Type-model</div> <div>Panel</div> <div>Viewable image size</div> <div>Max view area (W x H)</div> <div>Optimum resolution</div> <div>Maximum resolution</div> <div>Aspect ratio</div> <div>Pixel pitch (mm)</div> <div>Dot/Pixel per Inch</div> <div>Brightness</div> <div>Contrast ratio</div> <div>Pixel response time</div> <div>Color gamut</div> <div>Anti-reflective</div> <div>Vertical frequency</div> <div>Horizontal frequency</div> <div>Viewing angle at 10:1 CR</div> <div>Stand</div> <div>Bezel width</div> <div>Dimensions (HxWxD)</div> <div>Power supply</div> <div>Weight</div> <div>Limited warranty<sup>4</sup></div> <div>Available date</div>	<div>L1900p Flat Panel Monitor</div> <div>Business black</div> <div>4431-HE1</div> <div>TFT-LCD, twisted nematic (TN), CCFL backlight</div> <div>19.0" (483mm) diagonal</div> <div>14.8" x 11.85" (376mm x 301mm)</div> <div>1280x1024 at 60Hz</div> <div>1280x1024 at 75Hz (135MHz max pixel rate)</div> <div>5:4</div> <div>.294mm</div> <div>86 dpi</div> <div>250 nits or cd/m<sup>2</sup> (typical)</div> <div>800:1 (typical)</div> <div>5ms (typical)</div> <div>72%</div> <div>Anti-reflective, anti-glare</div> <div>56 to 76Hz</div> <div>30 to 81kHz</div> <div>160° (+/- 80°) horizontal, 160° (+/- 80°) vertical</div> <div>Tilt, swivel, pivot, and height adjustable stand</div> <div>Sides: 0.6" (15.3mm); top: 0.66" (16.8mm); bottom: 1.05" (26.8mm)</div> <div>14.9-19.2" H x 16.1" W x 7.4-9.5" D; 378.7-488.7mm H x 408mm W x 188-241.1mm D</div> <div>17 watts typical, 24 watts maximum, &lt;1 watts standby/suspend, universal, integrated (no external brick-like power supply)</div> <div>12.5 lb; 5.7kg</div> <div>3 year (includes backlight)</div> <div>November 2008</div>
<div>VESA-compliant<sup>2</sup></div> <div>Power management</div> <div>Ergonomics</div> <div>Pixel defect</div> <div>Emission standards</div> <div>Environmental</div>	<div>VESA DDC2B/CI, VESA DPMS-compliant</div> <div>ENERGY STAR<sup>®3</sup> 5.0</div> <div>ISO 13406 Part 2<sup>1</sup></div> <div>ISO 13406-2 Class II pixel defect standard</div> <div>MPR-2, MPR-3A, FCC Class B</div> <div>TCO 03, WEEE, RoHS (EU Directive 2002/95/EC), EPEAT™ Gold rating, GREENGUARD<sup>®</sup> certified</div>
<div>Preset resolutions</div> <div>Presets / user settings</div>	<div>VGA: 640x350, 640x480, 720x400</div> <div>SVGA: 800x600</div> <div>XGA: 1024x768</div> <div>SXGA: 1280x1024</div> <div>Standard presets: 21; user settings: 17</div>
<div>Viewing adjustments</div> <div>Rotating screen</div> <div>On screen display</div> <div>Control features</div> <div>Multiple input</div> <div>Monitor connectors</div> <div>Signal cables</div> <div>Mounting features</div> <div>Security</div>	<div>Tilt: 30° back, 0° forward; lift: 4.3" (110mm); swivel: +/-45°; detachable stand</div> <div>Screen pivots 90 degrees from landscape to portrait (requires image rotation support from graphics controller)</div> <div>On screen display with digital user controls (8 languages)</div> <div>Direct access (buttons on front) for automatic image setup</div> <div>Multiple input (two different PCs attach to two different connectors; one PC shows image; select via button)</div> <div>(1) VGA 15-pin D-shell, analog, blue</div> <div>(2) Digital Visual Interface (DVI-D), digital, white, <b>HDCP-compliant</b></div> <div>(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter</div> <div>(2) detachable, DVI-D at each end, digital, 1.8 meter</div> <div>Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI<sup>®</sup> (100mm mount)</div> <div>Security keyhole for attachment of optional cable lock (Kensington<sup>®</sup> lock-compatible)</div>
<div>Ship group</div>	<div>Monitor, attached stand, cable cover, Setup poster, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, 1.8 meter analog signal cable, 1.8 meter digital signal cable, 1.8 meter black power cord</div>

<div>Limited Warranty</div> <div>⇒ 3 year limited warranty<sup>4</sup></div> <div>⇒ International Warranty Service<sup>5</sup></div> <div>⇒ Rapid Replacement Service at 1-800-426-7378</div> <div>⇒ Replacement normally arrives in two business days, excluding holidays</div> <div>⇒ Lenovo pays all shipping costs for valid warranty claims<sup>6</sup></div> <div>⇒ Service upgrade options:<sup>7</sup></div> <div>• 3 year, on site exchange, Mon-Fri 9-5 with next day response (ThinkPlus™ part number 41C9209)</div> <div>• 3 year, on site exchange, 7 day x 24 hr with 4 hour response (41C9212)</div> <div>• 4 year, on site exchange, Mon-Fri 9-5 with next day response (41C9233)</div> <div>• 4 year, on site exchange, 7 day x 24 hr with 4 hour response (41C9216)</div> <div>• 4 year, mail exchange (51J0589)</div> <div>• 5 year, mail exchange (51J0590)</div> <div>⇒ 24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></div>	<div>Accessories</div> <div>ThinkVision Soundbar45K1263</div> <div>Kensington® MicroSaver® Cable Lock73P2582</div> <div>Kensington Twin Head Cable Lock45K1620</div> <div>Lenovo Easy Reach Monitor Stand55Y9258</div> <div>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a></div> <div>See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a></div>
--	---

<div>Name</div> <div>Case color</div> <div>Type-model</div> <div>Panel</div> <div>Viewable image size</div> <div>Max view area (W x H)</div> <div>Optimum resolution</div> <div>Maximum resolution</div> <div>Aspect ratio</div> <div>Pixel pitch (mm)</div> <div>Dot/Pixel per Inch</div> <div>Brightness</div> <div>Contrast ratio</div> <div>Pixel response time</div> <div>Color gamut</div> <div>Anti-reflective</div> <div>Vertical frequency</div> <div>Horizontal frequency</div> <div>Viewing angle at 10:1 CR</div> <div>Stand</div> <div>Bezel width</div> <div>Dimensions (HxWxD)</div> <div>Power supply</div> <div>Weight</div> <div>Limited warranty<sup>4</sup></div> <div>Available date</div>	<div>L1951p Wide Flat Panel Monitor</div> <div>Business black</div> <div>2448-HB6</div> <div>TFT-LCD, twisted nematic (TN), CCFL backlight</div> <div>19.0" (481mm) diagonal</div> <div>16.07" x 10.05" (408.2mm x 255.2mm)</div> <div>1440x900 at 60Hz</div> <div>1440x900 at 75Hz (137MHz max pixel rate)</div> <div>16:10</div> <div>.285mm</div> <div>89 dpi</div> <div>250 nits or cd/m<sup>2</sup> (typical)</div> <div>1000:1 (typical)</div> <div>5ms (typical)</div> <div>72%</div> <div>Anti-reflective, anti-glare</div> <div>50 to 76Hz</div> <div>30 to 81kHz</div> <div>160° (+/- 80°) horizontal, 160° (+/- 80°) vertical</div> <div>Tilt and height adjustable stand</div> <div>Sides: 0.61" (15.6mm); top: 0.67" (17.1mm); bottom: 1.2" (30.5mm)</div> <div>14.56-17.71" H x 17.36" W x 6.11" D; 369.9-449.9mm H x 440.9mm W x 155.2mm D</div> <div>19 watts typical, 23 watts maximum, &lt;1 watts standby/suspend, universal, integrated (no external brick-like power supply)</div> <div>9.37 lb; 4.25kg</div> <div>3 year (includes backlight)</div> <div>October 2009</div>	<div>Features</div> <div>• Widescreen 19-inch monitor</div> <div>• Supports WXGA+ 1440x900 resolution</div> <div>• Ergonomic stand tilts and provides a 3.1" (80mm) range height adjustment for comfortable viewing</div> <div>• Includes dual input connection for attachment to two systems concurrently (analog and digital)</div> <div>• Reduces mercury content by 50% and arsenic free glass</div> <div>• Up to 70% recycled packaging materials</div> <div>• Privacy Filter Slot</div> <div>• Microsoft® Windows® 7 certified</div>
<div>VESA-compliant<sup>2</sup></div> <div>Power management</div> <div>Ergonomics</div> <div>Emission standards</div> <div>Environmental</div>	<div>VESA DDC2B/CI, VESA DPMS-compliant</div> <div>ENERGY STAR® 5.0</div> <div>ISO 9241-307</div> <div>MPR-2, MPR-3A, FCC Class B</div> <div>TCO (TCO Displays 5.0), WEEE, RoHS,</div> <div>EPEAT™ Gold rating</div>	<div></div> <div>ThinkVision L1951p Wide Monitor</div>
<div>Preset resolutions</div>	<div>VGA: 640x350, 640x480, 720x400</div> <div>SVGA: 800x600, 832x624</div> <div>XGA: 1024x768, 1152x864</div> <div>SXGA: 1280x1024</div> <div>WXGA: 1280x720, 1360x768</div> <div>WXGA+ 1440x900</div>	
<div>Presets / user settings</div>	<div>Standard presets: 27;</div> <div>user settings: 20</div>	
<div>Viewing adjustments</div> <div>Rotating screen</div> <div>On screen display</div> <div>Control features</div> <div>Multiple input</div> <div>Monitor connectors</div> <div>Signal cables</div> <div>Mounting features</div> <div>Security</div>	<div>Tilt: 20° back, -3° forward; lift: 3.1" (80mm); detachable stand</div> <div>None</div> <div>On screen display with digital user controls (8 languages)</div> <div>Direct access (buttons on front) for automatic image setup</div> <div>Dual input (two different PCs attach to two different connectors; one PC shows image; select via button)</div> <div>(1) VGA 15-pin D-shell, analog, blue</div> <div>(2) Digital Visual Interface (DVI-D), digital, white, <b>HDCP-compliant</b></div> <div>(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter</div> <div>(2) detachable, DVI-D at each end, digital, 1.8 meter</div> <div>Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount)</div> <div>Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</div>	
<div>Ship group</div>	<div>Monitor, attached stand, Setup poster, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, 1.8 meter analog signal cable, 1.8 meter digital signal cable, 1.8 meter black power cord</div>	
<div>Limited Warranty</div> <div>⇒ 3 year limited warranty<sup>4</sup></div> <div>⇒ International Warranty Service<sup>5</sup></div> <div>⇒ Rapid Replacement Service at 1-800-426-7378</div> <div>⇒ Replacement normally arrives in two business days, excluding holidays</div> <div>⇒ Lenovo pays all shipping costs for valid warranty claims<sup>6</sup></div> <div>⇒ Service upgrade options:<sup>7</sup></div> <div>• 3 year, on site exchange, Mon-Fri 9-5 with next day response (ThinkPlus™ part number 41C9209)</div> <div>• 3 year, on site exchange, 7 day x 24 hr with 4 hour response (41C9212)</div> <div>• 4 year, on site exchange, Mon-Fri 9-5 with next day response (41C9233)</div> <div>• 4 year, on site exchange, 7 day x 24 hr with 4 hour response (41C9216)</div> <div>• 4 year, mail exchange (51J0589)</div> <div>• 5 year, mail exchange (51J0590)</div> <div>⇒ 24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></div>		
<div>Accessories</div> <div>ThinkVision Soundbar45K1263</div> <div>Kensington® MicroSaver® Cable Lock73P2582</div> <div>Kensington Twin Head Cable Lock45K1620</div> <div>Lenovo Easy Reach Monitor Stand55Y9258</div> <div>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a></div> <div>See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a></div>		




<p>Name <b>LT1952p Wide Flat Panel Monitor</b>                  Case color <b>Business black</b>                  Type-model <b>2448-MB6</b>                  Panel TFT-LCD, twisted nematic (TN), White LED backlight                  Viewable image size <b>19" (482.6mm)</b> diagonal                  Max view area (W x H) <b>16.07" x 10.05" (408.2mm x 255.2mm)</b>                  Optimum resolution <b>1440x900</b>                  Max pixel rate <b>137MHz</b>                  Aspect ratio <b>16:10</b>                  Pixel pitch (mm) <b>0.2835mm</b>                  Dot/Pixel per Inch <b>89.4 dpi</b>                  Brightness <b>250 nits or cd/m<sup>2</sup> (typical)</b>                  Contrast ratio <b>1000:1 (typical)</b>                  Pixel response time <b>5ms (typical)</b>                  Color gamut <b>72%</b>                  Anti-reflective <b>Anti-reflective, anti-glare</b>                  Viewing angle at 10:1 CR <b>170° horizontal, 160° vertical</b>                  Stand <b>Tilt, swivel, and height adjustable stand</b>                  Bezel width <b>Sides: 0.61" (15.6mm); top: 0.67" (17.1mm); bottom: 1.2" (30.5mm)</b>                  Dimensions (HxWxD) <b>15.66-19.99" H x 17.36" W x 6.74" D; 397.7-507.7mm H x 440.9mm W x 171.3mm D</b>                  Power supply <b>13 watts typical, 17 watts maximum, &lt;0.5 watts standby/suspend, universal, integrated (no external brick-like power supply)</b>                  Weight <b>9.49 lb; 4.30kg</b>                  Limited warranty<sup>4</sup> <b>3 year (includes backlight)</b>                  Available date <b>September 2011</b></p>	<p><b>Features</b></p> <ul style="list-style-type: none"> <li>• Widescreen 19-inch monitor</li> <li>• Supports 1440x900 resolution</li> <li>• Ergonomic stand tilts, swivel, and provides a 4.3" (110mm) range height adjustment for comfortable viewing</li> <li>• Cable Management for better user experience</li> <li>• Mercury and arsenic free glass</li> <li>• Recycled content in plastic material</li> <li>• Privacy Filter Slot</li> <li>• Microsoft® Windows® 7 certified</li> </ul>														
<p>VESA-compliant<sup>2</sup> <b>VESA DDC2B/CI</b>                  Power management <b>ENERGY STAR® 5.1</b>                  Ergonomics <b>ISO 9241-307</b>                  Emission standards <b>MPR-2, FCC Class B</b>                  Environmental <b>TCO Displays 5.2, TCO Certified Edge 1.1, WEEE, RoHS, EPEAT™ Gold rating, ULE Gold</b></p>	 <p><b>ThinkVision LT1952p Wide Monitor</b></p>														
<p>Preset resolutions <b>VGA: 640x350, 640x480, 720x400                  SVGA: 800x600                  XGA: 1024x768, 1152x864                  SXGA: 1280x1024                  WXGA: 1280x768, 1366x768                  WXGA+: 1440x900</b>                  Presets / user settings <b>Standard presets: 22; user settings: 22</b></p>															
<p>Viewing adjustments <b>Tilt: 20° back, -3° forward; lift: 4.3" (110mm); swivel: +/-180°; detachable stand</b>                  Rotating screen <b>None</b>                  On screen display <b>On screen display with digital user controls (8 languages)</b>                  Control features <b>Direct access (buttons on front) for automatic image setup, input switch, and brightness</b>                  Multiple input <b>Triple input (three different PCs attach to three different connectors; one PC shows image; select via button)</b>                  Monitor connectors <b>(1) VGA 15-pin D-shell, analog, blue                  (2) DisplayPort, digital, black, HDCP-compliant                  (3) Digital Visual Interface (DVI-D), digital, white, <b>HDCP-compliant</b></b>                  Signal cables <b>(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter                  (2) detachable, DVI-D at each end, digital, 1.8 meter                  Note: DisplayPort cable is not included; use optional DisplayPort to DisplayPort Monitor Cable (0A36537)</b>                  Mounting features <b>Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount)</b>                  Security <b>Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</b></p>															
<p>Ship group <b>Monitor, attached stand, Setup poster, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, 1.8 meter analog signal cable, 1.8 meter DVI-D cable, 1.8 meter black power cord</b></p>	<p><b>Accessories</b></p> <table> <tr> <td>DisplayPort to DisplayPort Monitor Cable</td> <td>0A36537</td> </tr> <tr> <td>ThinkVision Soundbar</td> <td>45K1263</td> </tr> <tr> <td>Kensington MicroSaver Cable Lock</td> <td>73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td>45K1620</td> </tr> <tr> <td>Lenovo Security Cable Lock</td> <td>57Y4303</td> </tr> <tr> <td>ThinkCentre Extend Arm</td> <td>57Y4352</td> </tr> <tr> <td>Lenovo Easy Reach Monitor Stand</td> <td>55Y9258</td> </tr> </table> <p>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a></p> <p>See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a></p>	DisplayPort to DisplayPort Monitor Cable	0A36537	ThinkVision Soundbar	45K1263	Kensington MicroSaver Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620	Lenovo Security Cable Lock	57Y4303	ThinkCentre Extend Arm	57Y4352	Lenovo Easy Reach Monitor Stand	55Y9258
DisplayPort to DisplayPort Monitor Cable	0A36537														
ThinkVision Soundbar	45K1263														
Kensington MicroSaver Cable Lock	73P2582														
Kensington Twin Head Cable Lock	45K1620														
Lenovo Security Cable Lock	57Y4303														
ThinkCentre Extend Arm	57Y4352														
Lenovo Easy Reach Monitor Stand	55Y9258														
<p><b>Limited Warranty</b></p> <ul style="list-style-type: none"> <li>⇒ <b>3 year limited warranty<sup>4</sup></b></li> <li>⇒ <b>International Warranty Service<sup>5</sup></b></li> <li>⇒ <b>Rapid Replacement Service at 1-800-426-7378</b></li> <li>⇒ <b>Replacement normally arrives in two business days, excluding holidays</b></li> <li>⇒ <b>Lenovo pays all shipping costs for valid warranty claims<sup>6</sup></b></li> <li>⇒ <b>Service upgrade options:<sup>7</sup></b> <ul style="list-style-type: none"> <li>• <b>3 year, on site exchange, Mon-Fri 9-5 with next day response</b> (ThinkPlus™ part number 41C9209)</li> <li>• <b>3 year, on site exchange, 7 day x 24 hr with 4 hour response</b> (41C9212)</li> <li>• <b>4 year, on site exchange, Mon-Fri 9-5 with next day response</b> (41C9233)</li> <li>• <b>4 year, on site exchange, 7 day x 24 hr with 4 hour response</b> (41C9216)</li> <li>• <b>4 year, mail exchange</b> (51J0589)</li> <li>• <b>5 year, mail exchange</b> (51J0590)</li> </ul> </li> <li>⇒ <b>24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></b></li> </ul>	<p>See footnotes for important warranty information                  US model announced September 13, 2011</p>														


See footnotes for important warranty information  
 US model announced September 13, 2011

© Lenovo  
 (LT1952P) September 2011




<b>Name</b> <b>Case color</b> <b>Type-model</b> <b>Panel</b> <b>Viewable image size</b> <b>Max view area (W x H)</b> <b>Optimum resolution</b> <b>Maximum resolution</b> <b>Aspect ratio</b> <b>Pixel pitch (mm)</b> <b>Dot/Pixel per Inch</b> <b>Brightness</b> <b>Contrast ratio</b> <b>Pixel response time</b> <b>Color gamut</b> <b>Anti-reflective</b> <b>Vertical frequency</b> <b>Horizontal frequency</b> <b>Viewing angle at 10:1 CR</b> <b>Stand</b> <b>Bezel width</b> <b>Dimensions (HxWxD)</b> <b>Power supply</b> <b>Weight</b> <b>Limited warranty<sup>4</sup></b> <b>Available date</b>	<b>L2250p Wide Flat Panel Monitor</b> <b>Business black</b> <b>2572-HB6</b> TFT-LCD, twisted nematic (TN), CCFL backlight <b>22.0" (559mm)</b> diagonal 18.7" x 11.7" (473.8mm x 296.1mm) <b>1680x1050</b> at 60Hz 1680x1050 at 75Hz (205MHz max pixel rate) 16:10 .282mm 90 dpi 250 nits or cd/m <sup>2</sup> (typical) 1000:1 (typical) 5ms (typical) 72% Anti-reflective, anti-glare 50 to 75Hz 30 to 83kHz 170° (+/- 85°) horizontal, 160° (+/- 80°) vertical Tilt and height adjustable stand <i>Sides: 0.60" (15.3mm); top: 0.79" (20.0mm); bottom: 1.10" (28.0mm)</i> 15.68-18.83" H x 19.92" W x 6.11" D; 398.3-478.3mm H x 506mm W x 155.2mm D 21 watts typical, 28 watts maximum, <1 watts standby/suspend, universal, integrated (no external brick-like power supply) 11.49 lb; 5.21kg <b>3 year</b> (includes backlight) October 2009
<b>VESA-compliant<sup>2</sup></b> <b>Power management</b> <b>Ergonomics</b> <b>Emission standards</b> <b>Environmental</b>	<b>Features</b> <ul style="list-style-type: none"> <li>• Widescreen 22-inch monitor</li> <li>• Supports WSXGA+ 1680x1050 resolution</li> <li>• Ergonomic stand tilts and provides a 3.1" (80mm) range height adjustment for comfortable viewing</li> <li>• Includes dual input connection for attachment to two systems concurrently (analog and digital)</li> <li>• Reduces mercury content by 50% and arsenic free glass</li> <li>• Up to 65% recycled packaging materials</li> <li>• Privacy Filter Slot</li> <li>• Microsoft® Windows® 7 certified</li> </ul>
<b>Preset resolutions</b> <b>Presets / user settings</b>	 <b>ThinkVision L2250p Wide Monitor</b>
<b>Viewing adjustments</b> <b>Rotating screen</b> <b>On screen display</b> <b>Control features</b> <b>USB hub</b> <b>Camera</b> <b>Multiple input</b> <b>Monitor connectors</b> <b>Signal cables</b> <b>Mounting features</b> <b>Security</b>	VGA: 640x350, 640x480, 720x480 SVGA: 800x600 XGA: 1024x768, 1152x864 SXGA: 1280x1024 WXGA+: 1440x900 UXGA: 1600x1000 WSXGA+: 1680x1050 Standard presets: 24; user settings: 20 <i>Tilt: 20° back, -3° forward; lift: 3.1" (80mm); detachable stand</i> None On screen display with digital user controls (8 languages) Direct access (buttons on front) for automatic image setup None None Dual input (two different PCs attach to two different connectors; one PC shows image; select via button) (1) VGA 15-pin D-shell, analog, blue (2) Digital Visual Interface (DVI-D), digital, white, <b>HDCP-compliant</b> (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, DVI-D at each end, digital, 1.8 meter Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount) Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)
<b>Ship group</b>	Monitor, attached stand, Setup poster, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, 1.8 meter analog signal cable, 1.8 meter digital signal cable, 1.8 meter black power cord

<b>Limited Warranty</b> ⇒ <b>3 year limited warranty<sup>4</sup></b> ⇒ <b>International Warranty Service<sup>5</sup></b> ⇒ <b>Rapid Replacement Service at 1-800-426-7378</b> ⇒ <b>Replacement normally arrives in two business days, excluding holidays</b> ⇒ <b>Lenovo pays all shipping costs for valid warranty claims<sup>6</sup></b> ⇒ <b>Service upgrade options:<sup>7</sup></b> <ul style="list-style-type: none"> <li>• <b>3 year, on site exchange, Mon-Fri 9-5 with next day response</b> (ThinkPlus™ part number 41C9209)</li> <li>• <b>3 year, on site exchange, 7 day x 24 hr with 4 hour response</b> (41C9212)</li> <li>• <b>4 year, on site exchange, Mon-Fri 9-5 with next day response</b> (41C9233)</li> <li>• <b>4 year, on site exchange, 7 day x 24 hr with 4 hour response</b> (41C9216)</li> <li>• <b>4 year, mail exchange</b> (51J0589)</li> <li>• <b>5 year, mail exchange</b> (51J0590)</li> </ul> ⇒ <b>24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></b>	<b>Accessories</b> <table> <tr> <td>ThinkVision Soundbar</td> <td>45K1263</td> </tr> <tr> <td>Kensington MicroSaver® Cable Lock</td> <td>73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td>45K1620</td> </tr> <tr> <td>Lenovo Easy Reach Monitor Stand</td> <td>55Y9258</td> </tr> </table> <p>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a></p> <p>See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a></p>	ThinkVision Soundbar	45K1263	Kensington MicroSaver® Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620	Lenovo Easy Reach Monitor Stand	55Y9258
ThinkVision Soundbar	45K1263								
Kensington MicroSaver® Cable Lock	73P2582								
Kensington Twin Head Cable Lock	45K1620								
Lenovo Easy Reach Monitor Stand	55Y9258								

<div>Name</div> <div>Case color</div> <div>Type-model</div> <div>Panel</div> <div>Viewable image size</div> <div>Max view area (W x H)</div> <div>Optimum resolution</div> <div>Maximum resolution</div> <div>Aspect ratio</div> <div>Pixel pitch (mm)</div> <div>Dot/Pixel per Inch</div> <div>Brightness</div> <div>Contrast ratio</div> <div>Pixel response time</div> <div>Color gamut</div> <div>Anti-reflective</div> <div>Vertical frequency</div> <div>Horizontal frequency</div> <div>Viewing angle at 10:1 CR</div> <div>Stand</div> <div>Bezel width</div> <div>Dimensions (HxWxD)</div> <div>Power supply</div> <div>Weight</div> <div>Limited warranty<sup>4</sup></div> <div>Available date</div>	<div>L2251p Wide Flat Panel Monitor</div> <div>Business black</div> <div>2572-HD6</div> <div>TFT-LCD, twisted nematic (TN), CCFL backlight</div> <div>22.0" (559mm) diagonal</div> <div>18.7" x 11.7" (473.8mm x 296.1mm)</div> <div>1680x1050 at 60Hz</div> <div>1680x1050 at 75Hz (205MHz max pixel rate)</div> <div>16:10</div> <div>.282mm</div> <div>90 dpi</div> <div>250 nits or cd/m<sup>2</sup> (typical)</div> <div>1000:1 (typical)</div> <div>5ms (typical)</div> <div>72%</div> <div>Anti-reflective, anti-glare</div> <div>50 to 75Hz</div> <div>30 to 83kHz</div> <div>170° (+/- 85°) horizontal, 160° (+/- 80°) vertical</div> <div>Tilt, swivel, pivot, and height adjustable stand</div> <div>Sides: 0.60" (15.3mm); top: 0.79" (20.0mm); bottom: 1.10" (28.0mm)</div> <div>14.46-18.79" H x 19.92" W x 9.50" D; 367.3-477.3mm H x 506mm W x 241.2mm D</div> <div>21 watts typical, 28 watts maximum, &lt;1 watts standby/suspend, universal, integrated (no external brick-like power supply)</div> <div>12.94 lb; 5.88kg</div> <div>3 year (includes backlight)</div> <div>October 2009</div>	<div>Features</div> <div>• Widescreen 22-inch monitor</div> <div>• Supports WSXGA+ 1680x1050 resolution</div> <div>• Ergonomic stand tilts, swivels, pivots and provides a 4.3" (110mm) range height adjustment for comfortable viewing</div> <div>• Detachable rear stand cable cover and clip to hide cables</div> <div>• Reduces mercury content by 50% and arsenic free glass</div> <div>• Up to 60% recycled packaging materials</div> <div>• Privacy Filter Slot</div> <div>• Microsoft® Windows® 7 certified</div>
<div>VESA-compliant<sup>2</sup></div> <div>Power management</div> <div>Ergonomics</div> <div>Emission standards</div> <div>Environmental</div> <div>Preset resolutions</div> <div>Presets / user settings</div> <div>Viewing adjustments</div> <div>Rotating screen</div> <div>On screen display</div> <div>Control features</div> <div>USB hub</div> <div>Camera</div> <div>Multiple input</div> <div>Monitor connectors</div> <div>Signal cables</div> <div>Mounting features</div> <div>Security</div> <div>Ship group</div>	<div>VESA DDC2B/CI, VESA DPMS-compliant</div> <div>ENERGY STAR<sup>®3</sup> 5.0</div> <div>ISO 9241-307</div> <div>MPR-2, MPR-3A, FCC Class B</div> <div>TCO (TCO Displays 5.0), WEEE, RoHS, EPEAT™ Gold rating</div> <div>VGA: 640x350, 640x480, 720x400</div> <div>SVGA: 800x600</div> <div>XGA: 1024x768, 1152x864</div> <div>SXGA: 1280x1024</div> <div>WXGA+: 1440x900</div> <div>UXGA: 1600x1000</div> <div>WSXGA+: 1680x1050</div> <div>Standard presets: 24; user settings: 20</div> <div>Tilt: 30° back, 0° forward; lift: 4.3" (110mm); swivel: +/-45°; detachable stand</div> <div>Screen pivots 90 degrees from landscape to portrait (requires image rotation support from graphics controller)</div> <div>On screen display with digital user controls (8 languages)</div> <div>Direct access (buttons on front) for automatic image setup</div> <div>None</div> <div>None</div> <div>Dual input (two different PCs attach to two different connectors; one PC shows image; select via button)</div> <div>(1) VGA 15-pin D-shell, analog, blue</div> <div>(2) DisplayPort, digital, black, HDCP-compliant</div> <div>(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter</div> <div>(2) detachable, DisplayPort at each end, digital, 1.8 meter</div> <div>Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount)</div> <div>Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</div> <div>Monitor, attached stand, cable cover, Setup poster, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, 1.8 meter analog signal cable, 1.8 meter DisplayPort cable, 1.8 meter black power cord</div>	<div></div> <div>ThinkVision L2251p Wide Monitor</div>
<div>Limited Warranty</div> <div>⇒ 3 year limited warranty<sup>4</sup></div> <div>⇒ International Warranty Service<sup>5</sup></div> <div>⇒ Rapid Replacement Service at 1-800-426-7378</div> <div>⇒ Replacement normally arrives in two business days, excluding holidays</div> <div>⇒ Lenovo pays all shipping costs for valid warranty claims<sup>6</sup></div> <div>⇒ Service upgrade options:<sup>7</sup></div> <div>• 3 year, on site exchange, Mon-Fri 9-5 with next day response (ThinkPlus™ part number 41C9209)</div> <div>• 3 year, on site exchange, 7 day x 24 hr with 4 hour response (41C9212)</div> <div>• 4 year, on site exchange, Mon-Fri 9-5 with next day response (41C9233)</div> <div>• 4 year, on site exchange, 7 day x 24 hr with 4 hour response (41C9216)</div> <div>• 4 year, mail exchange (51J0589)</div> <div>• 5 year, mail exchange (51J0590)</div> <div>⇒ 24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></div>	<div>Accessories</div> <div>ThinkVision Soundbar</div> <div>Kensington® MicroSaver® Cable Lock</div> <div>Kensington Twin Head Cable Lock</div> <div>Lenovo Easy Reach Monitor Stand</div> <div>45K1263</div> <div>73P2582</div> <div>45K1620</div> <div>55Y9258</div> <div>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a></div> <div>See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a></div>	

<p>Name <b>LT2252p Wide Flat Panel Monitor</b>                  Case color <b>Business black</b>                  Type-model <b>2572-MB6</b>                  Panel TFT-LCD, twisted nematic (TN), White LED backlight                  Viewable image size <b>22" (559mm)</b> diagonal                  Max view area (W x H) <b>18.7" x 11.7"</b> (473.8mm x 296.1mm)                  Optimum resolution <b>1680x1050</b>                  Max pixel rate 205MHz                  Aspect ratio 16:10                  Pixel pitch (mm) 0.282mm                  Dot/Pixel per Inch 90 dpi                  Brightness 250 nits or cd/m<sup>2</sup> (typical)                  Contrast ratio 1000:1 (typical)                  Pixel response time 5ms (typical)                  Color gamut 72%                  Anti-reflective Anti-reflective, anti-glare                  Viewing angle at 10:1 CR 170° horizontal, 160° vertical                  Stand Tilt, swivel, pivot, and height adjustable stand                  Bezel width <i>Sides: 0.60" (15.3mm); top: 0.79" (20.0mm); bottom: 1.10" (28.0mm)</i></p> <p>Dimensions (HxWxD) 14.46-18.79" H x 19.92" W x 9.50" D;                  367.3-477.3mm H x 506mm W x 241.2mm D</p> <p>Power supply 20 watts typical, 26 watts maximum,                  &lt;0.5 watts standby/suspend, universal,                  integrated (no external brick-like power supply)                  12.97lb; 5.89kg</p> <p>Weight                  Limited warranty<sup>4</sup> <b>3 year</b> (includes backlight)                  Available date September 2011</p>	<p><b>Features</b></p> <ul style="list-style-type: none"> <li>• Widescreen 22-inch monitor</li> <li>• Supports 1680x1050 resolution</li> <li>• Ergonomic stand tilts, swivels, pivots and provides a 4.3" (110mm) range height adjustment for comfortable viewing</li> <li>• Cable Management for better user experience</li> <li>• Mercury and arsenic free glass</li> <li>• Recycled content in plastic material</li> <li>• Privacy Filter Slot</li> <li>• Microsoft® Windows® 7 certified</li> </ul>															
<p>VESA-compliant<sup>2</sup> VESA DDC2B/CI                  Power management ENERGY STAR<sup>®</sup> 5.1                  Ergonomics ISO 9241-307                  Emission standards MPR-2, FCC Class B                  Environmental TCO Displays 5.2, TCO Certified Edge 1.1, WEEE, RoHS, <b>EPEAT™ Gold rating</b>, ULE Gold</p>	 <p><b>ThinkVision LT2252p Wide Monitor</b></p>															
<p>Preset resolutions</p> <table> <tr><td>VGA:</td><td>640x350, 640x480, 720x400</td></tr> <tr><td>SVGA:</td><td>800x600</td></tr> <tr><td>XGA:</td><td>1024x768, 1152x864</td></tr> <tr><td>SXGA:</td><td>1280x1024</td></tr> <tr><td>WXGA:</td><td>1280x768, 1280x800, 1366x768</td></tr> <tr><td>WXGA+:</td><td>1440x900</td></tr> <tr><td>WSXGA+:</td><td>1600x900</td></tr> <tr><td>WSXGA+:</td><td>1680x1050</td></tr> </table> <p>Presets / user settings</p> <p>Standard presets: <i>VGA/DisplayPort: 26; DVI-D: 25; user settings: 25</i></p>		VGA:	640x350, 640x480, 720x400	SVGA:	800x600	XGA:	1024x768, 1152x864	SXGA:	1280x1024	WXGA:	1280x768, 1280x800, 1366x768	WXGA+:	1440x900	WSXGA+:	1600x900	WSXGA+:
VGA:	640x350, 640x480, 720x400															
SVGA:	800x600															
XGA:	1024x768, 1152x864															
SXGA:	1280x1024															
WXGA:	1280x768, 1280x800, 1366x768															
WXGA+:	1440x900															
WSXGA+:	1600x900															
WSXGA+:	1680x1050															
<p>Viewing adjustments <i>Tilt: 30° back, 0° forward; lift: 4.3" (110mm); swivel: +/-45°; detachable stand</i>                  Rotating screen <b>Screen pivots 90 degrees from landscape to portrait</b> (requires image rotation support from graphics controller)                  On screen display On screen display with digital user controls (8 languages)                  Control features Direct access (buttons on front) for automatic image setup, input switch, and brightness                  USB hub None                  Camera None                  Multiple input Triple input (three different PCs attach to three different connectors; one PC shows image; select via button)                  Monitor connectors (1) VGA 15-pin D-shell, analog, blue                  (2) DisplayPort, digital, black, <b>HDCP-compliant</b>                  (3) Digital Visual Interface (DVI-D) for digital attach [white], <b>HDCP-compliant</b></p> <p>Signal cables (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter                  (2) detachable, DVI-D at each end, digital, 1.8 meter                  Note: DisplayPort cable is not included; use optional DisplayPort to DisplayPort Monitor Cable (0A36537)</p> <p>Mounting features Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI<sup>®</sup> (100mm mount)                  Security Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</p>	<p>Viewing adjustments <i>Tilt: 30° back, 0° forward; lift: 4.3" (110mm); swivel: +/-45°; detachable stand</i>                  Rotating screen <b>Screen pivots 90 degrees from landscape to portrait</b> (requires image rotation support from graphics controller)                  On screen display On screen display with digital user controls (8 languages)                  Control features Direct access (buttons on front) for automatic image setup, input switch, and brightness                  USB hub None                  Camera None                  Multiple input Triple input (three different PCs attach to three different connectors; one PC shows image; select via button)                  Monitor connectors (1) VGA 15-pin D-shell, analog, blue                  (2) DisplayPort, digital, black, <b>HDCP-compliant</b>                  (3) Digital Visual Interface (DVI-D) for digital attach [white], <b>HDCP-compliant</b></p> <p>Signal cables (1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter                  (2) detachable, DVI-D at each end, digital, 1.8 meter                  Note: DisplayPort cable is not included; use optional DisplayPort to DisplayPort Monitor Cable (0A36537)</p> <p>Mounting features Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI<sup>®</sup> (100mm mount)                  Security Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)</p>															
<p>Ship group</p> <p>Monitor, attached stand, cable cover, Setup poster, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, 1.8 meter analog signal cable, 1.8 meter DVI-D cable, 1.8 meter black power cord</p>																
<p><b>Limited Warranty</b></p> <p>⇒ <b>3 year limited warranty<sup>4</sup></b>                  ⇒ <b>International Warranty Service<sup>5</sup></b>                  ⇒ <b>Rapid Replacement Service at 1-800-426-7378</b>                  ⇒ <b>Replacement normally arrives in two business days, excluding holidays</b>                  ⇒ <b>Lenovo pays all shipping costs for valid warranty claims<sup>6</sup></b>                  ⇒ <b>Service upgrade options:<sup>7</sup></b></p> <ul style="list-style-type: none"> <li>• <b>3 year, on site exchange, Mon-Fri 9-5 with next day response</b> (ThinkPlus™ part number 41C9209)</li> <li>• <b>3 year, on site exchange, 7 day x 24 hr with 4 hour response</b> (41C9212)</li> <li>• <b>4 year, on site exchange, Mon-Fri 9-5 with next day response</b> (41C9233)</li> <li>• <b>4 year, on site exchange, 7 day x 24 hr with 4 hour response</b> (41C9216)</li> <li>• <b>4 year, mail exchange</b> (51J0589)</li> <li>• <b>5 year, mail exchange</b> (51J0590)</li> </ul> <p>⇒ <b>24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></b></p>	<p><b>Accessories</b></p> <table> <tr><td>DisplayPort to DisplayPort Monitor Cable</td><td>0A36537</td></tr> <tr><td>ThinkVision Soundbar</td><td>45K1263</td></tr> <tr><td>Kensington® MicroSaver® Cable Lock</td><td>73P2582</td></tr> <tr><td>Kensington Twin Head Cable Lock</td><td>45K1620</td></tr> <tr><td>Lenovo Security Cable Lock</td><td>57Y4303</td></tr> <tr><td>ThinkCentre Extend Arm</td><td>57Y4352</td></tr> <tr><td>Lenovo Easy Reach Monitor Stand</td><td>55Y9258</td></tr> </table> <p>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a></p> <p>See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a></p>	DisplayPort to DisplayPort Monitor Cable	0A36537	ThinkVision Soundbar	45K1263	Kensington® MicroSaver® Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620	Lenovo Security Cable Lock	57Y4303	ThinkCentre Extend Arm	57Y4352	Lenovo Easy Reach Monitor Stand	55Y9258	
DisplayPort to DisplayPort Monitor Cable	0A36537															
ThinkVision Soundbar	45K1263															
Kensington® MicroSaver® Cable Lock	73P2582															
Kensington Twin Head Cable Lock	45K1620															
Lenovo Security Cable Lock	57Y4303															
ThinkCentre Extend Arm	57Y4352															
Lenovo Easy Reach Monitor Stand	55Y9258															



<b>Name</b> <b>Case color</b> <b>Type-model</b> <b>Panel</b> <b>Viewable image size</b> <b>Max view area (W x H)</b> <b>Optimum resolution</b> <b>Maximum resolution</b> <b>Aspect ratio</b> <b>Pixel pitch (mm)</b> <b>Dot/Pixel per Inch</b> <b>Brightness</b> <b>Contrast ratio</b> <b>Pixel response time</b> <b>Color gamut</b> <b>Anti-reflective</b> <b>Vertical frequency</b> <b>Horizontal frequency</b> <b>Viewing angle at 10:1 CR</b> <b>Stand</b> <b>Bezel width</b>  <b>Dimensions (HxWxD)</b>  <b>Power supply</b>  <b>Weight</b> <b>Limited warranty<sup>4</sup></b> <b>Available date</b>	<b>L2251x Wide Flat Panel Monitor</b> <b>Business black</b> <b>2578-HB6</b> TFT-LCD, twisted nematic (TN), <b>white LED backlight</b> <b>22.0" (559mm)</b> diagonal 18.7" x 11.7" / 473.8mm x 296.1mm <b>1680x1050</b> at 60Hz 1680x1050 at 75Hz (205MHz max pixel rate) 16:10 .282mm 90 dpi 250 nits or cd/m <sup>2</sup> (typical) 1000:1 (typical) 5ms (typical) 68% Anti-reflective, anti-glare 50 to 75Hz 30 to 83kHz 170° (+/- 85°) horizontal, 160° (+/- 80°) vertical Tilt, swivel, pivot, and height adjustable stand <i>Sides: 0.60" (15.3mm); top: 0.79" (20.0mm); bottom: 1.10" (28.0mm)</i> 14.97-19.3" H x 19.92" W x 9.50" D; 380.3-490.3mm H x 506mm W x 241.2mm D 21 watts typical, 28 watts maximum, <1 watts standby/suspend, universal, integrated (no external brick-like power supply) 12.39 lb; 5.63kg <b>3 year</b> (includes backlight) November 2009	<b>Features</b> <ul style="list-style-type: none"> <li>• Widescreen 22-inch monitor with white LED backlight</li> <li>• Ergonomic stand tilts, swivels, pivots and provides a 4.3" (110mm) range height adjustment for comfortable viewing</li> <li>• Detachable rear stand cable cover and clip to hide cables</li> <li>• Integrated camera (3.0 megapixel) and microphone</li> <li>• Integrated ambient light sensor and a proximity sensor, save more energy and make viewing more comfortable</li> <li>• Low halogen, mercury free, and arsenic free glass, 92% recycled packaging materials</li> <li>• Privacy Filter Slot</li> <li>• Microsoft® Windows® 7 certified</li> </ul>
<b>VESA-compliant<sup>2</sup></b> <b>Power management</b> <b>Ergonomics</b> <b>Emission standards</b> <b>Environmental</b>	VESA DDC2B/CI, VESA DPMS-compliant ENERGY STAR <sup>®3</sup> 5.0 ISO 9241-307 MPR-2, MPR-3A, FCC Class B TCO (TCO Certified Edge), WEEE, RoHS, <b>EPEAT™ Gold rating</b>	
<b>Preset resolutions</b>	VGA: 640x350, 640x480, 720x400 SVGA: 800x600 XGA: 1024x768, 1152x864 SXGA: 1280x1024 WXGA+: 1440x900 UXGA: 1600x1000 WSXGA+: 1680x1050	<b>ThinkVision L2251x Wide Monitor</b>
<b>Presets / user settings</b>	Standard presets: 24; user settings: 20	
<b>Viewing adjustments</b> <b>Rotating screen</b> <b>On screen display</b> <b>Control features</b> <b>USB hub</b> <b>Camera</b> <b>Multiple input</b> <b>Monitor connectors</b>	<i>Tilt: 30° back, 0° forward; lift: 4.3" (110mm); swivel: +/-45°; detachable stand</i> <b>Screen pivots 90 degrees from landscape to portrait</b> (requires image rotation support from graphics controller) On screen display with digital user controls (8 languages) Direct access (buttons on front) for automatic image setup USB 2.0 Hub (1 port into PC, 3 ports for accessories) Integrated camera (3.0 megapixel) and microphone Dual input (two different PCs attach to two different connectors; one PC shows image; select via button)	
<b>Signal cables</b>	(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, DisplayPort at each end, digital, 1.8 meter	
<b>Mounting features</b> <b>Security</b>	Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount) Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)	
<b>Ship group</b>	Monitor, attached stand, cable cover, Setup poster, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, 1.8 meter analog signal cable, 1.8 meter DisplayPort cable, 1.8 meter USB cable, 1.8 meter black power cord	

<b>Limited Warranty</b> ➤ <b>3 year limited warranty<sup>4</sup></b> ➤ <b>International Warranty Service<sup>5</sup></b> ➤ <b>Rapid Replacement Service at 1-800-426-7378</b> ➤ <b>Replacement normally arrives in two business days, excluding holidays</b> ➤ <b>Lenovo pays all shipping costs for valid warranty claims<sup>6</sup></b> ➤ <b>Service upgrade options:<sup>7</sup></b> <ul style="list-style-type: none"> <li>• <b>3 year, on site exchange, Mon-Fri 9-5 with next day response</b> (ThinkPlus™ part number 41C9209)</li> <li>• <b>3 year, on site exchange, 7 day x 24 hr with 4 hour response</b> (41C9212)</li> <li>• <b>4 year, on site exchange, Mon-Fri 9-5 with next day response</b> (41C9233)</li> <li>• <b>4 year, on site exchange, 7 day x 24 hr with 4 hour response</b> (41C9216)</li> <li>• <b>4 year, mail exchange</b> (51J0589)</li> <li>• <b>5 year, mail exchange</b> (51J0590)</li> </ul> ➤ <b>24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></b>	<b>Accessories</b> <table> <tr> <td>ThinkVision Soundbar</td> <td>45K1263</td> </tr> <tr> <td>Kensington® MicroSaver® Cable Lock</td> <td>73P2582</td> </tr> <tr> <td>Kensington Twin Head Cable Lock</td> <td>45K1620</td> </tr> <tr> <td>Lenovo Easy Reach Monitor Stand</td> <td>55Y9258</td> </tr> </table> <p>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a></p> <p>See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a></p>	ThinkVision Soundbar	45K1263	Kensington® MicroSaver® Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620	Lenovo Easy Reach Monitor Stand	55Y9258
ThinkVision Soundbar	45K1263								
Kensington® MicroSaver® Cable Lock	73P2582								
Kensington Twin Head Cable Lock	45K1620								
Lenovo Easy Reach Monitor Stand	55Y9258								



Name	<b>L2321x Wide Flat Panel Monitor</b>	<b>Features</b> <ul style="list-style-type: none"><li>• Widescreen 23-inch monitor</li><li>• 1080p full HD support, HDCP-compliant</li><li>• Function as two monitors, hardware based solution provies 4 patterns of screen split (2:1, 1:1, 1:2, PIP modes).</li><li>• Ergonomic stand tilts, swivels, pivots and provides a 4.3" (110mm) range height adjustment for comfortable viewing</li><li>• Compliance with ENERGY STAR 5.0</li><li>• Arsenic free glass</li><li>• Microsoft® Windows® 7 certified</li></ul>						
Case color	<b>Business black</b>							
Type-model	<b>4014-HB6</b>	 <b>ThinkVision L2321x Wide Monitor</b>						
Panel	TFT-LCD, twisted nematic (TN), CCFL backlight							
Viewable image size	<b>23.0" (584mm)</b> diagonal							
Max view area (W x H)	20.04" x 11.28" / 509.2mm x 286.4mm							
Optimum resolution	<b>1920x1080</b>							
Dual screen function	Function as two monitors (need both VGA and DisplayPort connected), hardware based solution provies 4 patterns of screen split (2:1, 1:1, 1:2, PIP)							
Aspect ratio	16:9							
Pixel pitch (mm)	.265mm							
Dot/Pixel per Inch	96 dpi							
Brightness	250 nits or cd/m² (typical)							
Contrast ratio	1000:1 (typical)							
Pixel response time	5ms (typical)							
Color gamut	72%							
Anti-reflective	Anti-reflective, anti-glare							
Vertical frequency	50 to 75Hz							
Horizontal frequency	30 to 83kHz							
Viewing angle at 10:1 CR	170° (+/- 85°) horizontal, 160° (+/- 80°) vertical							
Stand	Tilt, swivel, pivot, and height adjustable stand							
Bezel width	<i>Sides: 0.69" (17.6mm); top: 0.72" (18.2mm); bottom: 0.79" (20.1mm)</i>							
Dimensions (HxWxD)	14.72-19.05" H x 21.49" W x 9.49" D; 373.9-483.9mm H x 545.9mm W x 241.1mm D							
Power supply	24 watts typical, 28 watts maximum, <1 watts standby/suspend, universal, integrated (no external brick-like power supply)							
Weight	14.75 lb; 6.69kg							
Limited warranty <sup>4</sup>	<b>3 year</b> (includes backlight)							
Available date	July 2010							
VESA-compliant <sup>2</sup>	VESA DDC2B/CI, VESA DPMS-compliant							
Power management	ENERGY STAR <sup>®3</sup> 5.0							
Ergonomics	ISO 9241-307							
Emission standards	MPR-2, FCC Class B							
Environmental	TCO (TCO Certified Edge), WEEE, RoHS, <b>EPEAT™ Gold rating</b>							
Preset resolutions	NTSC, PAL, 640x350, 640x480, 800x600, 832x624, 960x1080, 1024x768, 1152x864, 1280x1024, 1280x1080, 1366x768, 1440x900, 1680x1050, 1920x1080							
Dual image resolution	(2:1): 1280x1080 + 640x1080 (1:2): 640x1080 + 1280x1080 (1:1): 960x1080 + 960x1080 (PIP): 640x480 in 1920x1080							
Presets / user settings	Presets: 26(VGA), 25(DisplayPort); user settings: 20							
Viewing adjustments	<i>Tilt:</i> 30° back, 0° forward; <i>lift:</i> 4.3" (110mm); <i>swivel:</i> +/-45°; detachable stand							
Rotating screen	<b>Screen pivots 90 degrees from landscape to portrait</b> (requires image rotation support from graphics controller, do not support image rotation under dual image modes)							
On screen display	On screen display with digital user controls (8 languages)							
Control features	Direct access (buttons on front) for automatic image setup and image select (Dual image [2:1, 1:1, 1:2, PIP modes], Swap, Single VGA, and Single DisplayPort)							
USB hub	USB 2.0 Hub (1 port into PC, 4 ports for accessories)							
Multiple input	Dual input (two different PCs attach to two different connectors; one PC shows image; select via button)							
Monitor connectors	(1) VGA 15-pin D-shell, analog, blue (2) DisplayPort, digital, black, <b>HDCP-compliant</b>							
Signal cables	(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, DisplayPort at each end, digital, 1.8 meter							
Mounting features	Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount)							
Security	Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)							
Ship group	Monitor, attached stand, Setup poster, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, analog signal cable, DisplayPort cable, 1.8 meter USB cable, 1.8 meter black power cord							
<b>Limited Warranty</b> <ul style="list-style-type: none"><li>➤ <b>3 year limited warranty<sup>4</sup></b></li><li>➤ <b>International Warranty Service<sup>5</sup></b></li><li>➤ <b>Rapid Replacement Service at 1-800-426-7378</b></li><li>➤ <b>Replacement normally arrives in two business days, excluding holidays</b></li><li>➤ <b>Lenovo pays all shipping costs for valid warranty claims<sup>6</sup></b></li><li>➤ <b>Service upgrade options:<sup>7</sup></b><ul style="list-style-type: none"><li>• <b>3 year, on site exchange, Mon-Fri 9-5 with next day response</b> (ThinkPlus™ part number 41C9209)</li><li>• <b>3 year, on site exchange, 7 day x 24 hr with 4 hour response</b> (41C9212)</li><li>• <b>4 year, on site exchange, Mon-Fri 9-5 with next day response</b> (41C9233)</li><li>• <b>4 year, on site exchange, 7 day x 24 hr with 4 hour response</b> (41C9216)</li><li>• <b>4 year, mail exchange</b> (51J0589)</li><li>• <b>5 year, mail exchange</b> (51J0590)</li></ul></li><li>➤ <b>24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></b></li></ul>		<b>Accessories</b> <table><tr><td>ThinkVision Soundbar</td><td>45K1263</td></tr><tr><td>Kensington® MicroSaver® Cable Lock</td><td>73P2582</td></tr><tr><td>Kensington Twin Head Cable Lock</td><td>45K1620</td></tr></table> <p>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a></p> <p>See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a></p>	ThinkVision Soundbar	45K1263	Kensington® MicroSaver® Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620
ThinkVision Soundbar	45K1263							
Kensington® MicroSaver® Cable Lock	73P2582							
Kensington Twin Head Cable Lock	45K1620							

<b>Name</b> <b>Case color</b> <b>Type-model</b> <b>Panel</b> <b>Viewable image size</b> <b>Max view area (W x H)</b> <b>Optimum resolution</b> <b>Maximum resolution</b> <b>Aspect ratio</b> <b>Pixel pitch (mm)</b> <b>Dot/Pixel per Inch</b> <b>Brightness</b> <b>Contrast ratio</b> <b>Pixel response time</b> <b>Color gamut</b> <b>Anti-reflective</b> <b>Vertical frequency</b> <b>Horizontal frequency</b> <b>Viewing angle at 10:1 CR</b> <b>Stand</b> <b>Bezel width</b>  <b>Dimensions (HxWxD)</b>  <b>Power supply</b>  <b>Weight</b> <b>Limited warranty<sup>4</sup></b> <b>Available date</b>	<b>L2440p Wide Flat Panel Monitor</b> <b>Business black</b> <b>4420-HB2</b> TFT-LCD, twisted nematic (TN), CCFL backlight <b>24.0" (610mm)</b> diagonal 20.4" x 12.8" (518.4mm x 324.0mm) <b>1920x1200</b> at 60Hz 1920x1200 at 60Hz (205MHz max pixel rate) 16:10 .270mm 94 dpi 300 nits or cd/m <sup>2</sup> (typical) 1000:1 (typical) 5ms (typical) 72% Anti-reflective, anti-glare 50 to 75Hz 30 to 94kHz 170° (+/- 85°) horizontal, 160° (+/- 80°) vertical Tilt, swivel, pivot, and height adjustable stand <i>Sides: 0.78" (19.9mm); top: 0.78" (19.9mm); bottom: 1.12" (28.4mm)</i> 15.54-19.87" H x 22" W x 8.04-10.13" D; 394.8-504.8mm H x 559.6mm W x 204.3-257.3mm D 35 watts typical, 50 watts maximum, <1 watts standby/suspend, universal, integrated (no external brick-like power supply) 17.84 lb; 8.09kg <b>3 year</b> (includes backlight) October 2008	<b>Features</b> <ul style="list-style-type: none"> <li>• Widescreen 24-inch monitor</li> <li>• Supports WUXGA 1920x1200 resolution</li> <li>• High Definition (HD) ready; supports 1080p video</li> <li>• Ergonomic stand tilts, swivels, pivots and provides a 4.3" (110mm) range height adjustment for comfortable viewing</li> <li>• Detachable rear stand cable cover and clip to hide cables</li> <li>• Carrying handle</li> <li>• 65% recycled packaging materials</li> <li>• Microsoft® Windows® Vista® Premium certified</li> </ul>
<b>VESA-compliant<sup>2</sup></b> <b>Power management</b> <b>Ergonomics</b> <b>Pixel defect</b> <b>Emission standards</b> <b>Environmental</b>	VESA DDC2B/CI, VESA DPMS-compliant ENERGY STAR® 5.0 ISO 13406 Part 2 <sup>1</sup> ISO 13406-2 Class II pixel defect standard MPR-2, MPR-3A, FCC Class B TCO 03, WEEE, RoHS (EU Directive 2002/95/EC), <b>EPEAT™ Gold rating</b> , GREENGUARD® certified	
<b>Preset resolutions</b>	VGA: 640x350, 640x480, 720x400 SVGA: 800x600 XGA: 1024x768, 1152x864 SXGA: 1280x1024 WXGA: 1360x768 WXGA+: 1440x900 UXGA: 1600x1200 WSXGA+: 1680x1050 WUXGA: 1920x1200	
<b>Presets / user settings</b>	Standard presets: 27; user settings: 20	
<b>Viewing adjustments</b> <b>Rotating screen</b> <b>On screen display</b> <b>Control features</b> <b>USB hub</b> <b>Multiple input</b> <b>Monitor connectors</b>	<i>Tilt: 30° back, 0° forward; lift: 4.3" (110mm); swivel: +/-45°; detachable stand</i> <b>Screen pivots 90 degrees from landscape to portrait</b> (requires image rotation support from graphics controller), On screen display with digital user controls (8 languages) Direct access (buttons on front) for automatic image setup USB 2.0 Hub (1 port into PC, 4 ports for accessories) Multiple input (two different PCs attach to two different connectors; one PC shows image; select via button) (1) VGA 15-pin D-shell, analog, blue (2) Digital Visual Interface (DVI-D), digital, white, <b>HDCP-compliant</b>	
<b>Signal cables</b>	(1) detachable, VGA 15-pin D-shell at each end, analog, 2.2 meter (2) detachable, DVI-D at each end, digital, 2.2 meter	
<b>Mounting features</b> <b>Security</b>	Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount) Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)	
<b>Ship group</b>	Monitor, attached stand, cable cover, Setup poster, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, 2.2 meter analog signal cable, 2.2 meter digital signal cable, 2.2 meter USB cable, 1.8 meter black power cord	


**ThinkVision L2440p Wide Monitor**

<b>Limited Warranty</b> <ul style="list-style-type: none"> <li>⇒ <b>3 year limited warranty<sup>4</sup></b></li> <li>⇒ <b>International Warranty Service<sup>5</sup></b></li> <li>⇒ <b>Rapid Replacement Service at 1-800-426-7378</b></li> <li>⇒ <b>Replacement normally arrives in two business days, excluding holidays</b></li> <li>⇒ <b>Lenovo pays all shipping costs for valid warranty claims<sup>6</sup></b></li> <li>⇒ <b>Service upgrade options:<sup>7</sup></b> <ul style="list-style-type: none"> <li>• <b>3 year, on site exchange, Mon-Fri 9-5 with next day response</b> (ThinkPlus™ part number 41C9209)</li> <li>• <b>3 year, on site exchange, 7 day x 24 hr with 4 hour response</b> (41C9212)</li> <li>• <b>4 year, on site exchange, Mon-Fri 9-5 with next day response</b> (41C9233)</li> <li>• <b>4 year, on site exchange, 7 day x 24 hr with 4 hour response</b> (41C9216)</li> <li>• <b>4 year, mail exchange</b> (51J0589)</li> <li>• <b>5 year, mail exchange</b> (51J0590)</li> </ul> </li> <li>⇒ <b>24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></b></li> </ul>	<b>Accessories</b> <table> <tr> <td>ThinkVision Soundbar</td><td>45K1263</td></tr> <tr> <td>Kensington® MicroSaver® Cable Lock</td><td>73P2582</td></tr> <tr> <td>Kensington Twin Head Cable Lock</td><td>45K1620</td></tr> <tr> <td>Lenovo Easy Reach Monitor Stand</td><td>55Y9258</td></tr> </table> <p>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a></p> <p>See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a></p>	ThinkVision Soundbar	45K1263	Kensington® MicroSaver® Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620	Lenovo Easy Reach Monitor Stand	55Y9258
ThinkVision Soundbar	45K1263								
Kensington® MicroSaver® Cable Lock	73P2582								
Kensington Twin Head Cable Lock	45K1620								
Lenovo Easy Reach Monitor Stand	55Y9258								

<b>Name</b> <b>Case color</b> <b>Type-model</b> <b>Panel</b> <b>Viewable image size</b> <b>Max view area (W x H)</b> <b>Optimum resolution</b> <b>Max pixel rate</b> <b>Aspect ratio</b> <b>Pixel pitch (mm)</b> <b>Dot/Pixel per Inch</b> <b>Brightness</b> <b>Contrast ratio</b> <b>Pixel response time</b> <b>Color gamut</b> <b>Anti-reflective</b> <b>Viewing angle at 10:1 CR</b> <b>Stand</b> <b>Bezel width</b>  <b>Dimensions (HxWxD)</b>  <b>Power supply</b>   <b>Weight</b> <b>Limited warranty<sup>4</sup></b> <b>Available date</b>	<b>LT2452p Wide Flat Panel Monitor</b> <b>Business black</b> <b>4420-MB2</b> TFT-LCD, e-IPS, White LED backlight <b>24" (610mm)</b> diagonal 20.4" x 12.8" (518.4mm x 324.0mm) <b>1920x1200</b> 202.5MHz 16:10 0.270mm 94 dpi 300 nits or cd/m <sup>2</sup> (typical) 1000:1 (typical) 7ms (GtG) 72% Anti-reflective, anti-glare 178° horizontal, 178° vertical Tilt, swivel, pivot, and height adjustable stand <i>Sides: 0.78" (19.9mm); top: 0.78" (19.9mm); bottom: 1.12" (28.4mm)</i> 15.54-19.87" H x 22" W x 10.13" D; 394.8-504.8mm H x 559.6mm W x 257.3mm D 30 watts typical (w/o USB hub), 40 watts maximum (w/o USB hub), <0.5 watts standby/suspend (w/o USB hub), universal, integrated (no external brick-like power supply) 14.70 lb; 6.67kg <b>3 year</b> (includes backlight) September 2011	<b>Features</b> <ul style="list-style-type: none"> <li>• Widescreen 24-inch monitor</li> <li>• Supports 1920x1200 resolution</li> <li>• High Definition (HD) ready; supports 1080p video</li> <li>• Ergonomic stand tilts, swivels, pivots and provides a 4.3" (110mm) range height adjustment for comfortable viewing</li> <li>• Cable Management for better user experience</li> <li>• Carrying handle</li> <li>• Recycled content in plastic material</li> <li>• Microsoft® Windows® 7 certified</li> </ul>
<b>VESA-compliant<sup>2</sup></b> <b>Power management</b> <b>Ergonomics</b> <b>Emission standards</b> <b>Environmental</b>	VESA DDC2B/CI ENERGY STAR® 5.1 ISO 9241-307 MPR-2, FCC Class B TCO Displays 5.2, TCO Certified Edge 1.1, WEEE, RoHS, <b>EPEAT™ Gold rating</b> , ULE Gold	 <p>The image shows a black Lenovo ThinkVision LT2452p Wide Monitor. The screen displays a vibrant green abstract pattern. The monitor is mounted on a black stand with a circular base. The Lenovo logo is visible on the bottom bezel.</p>
<b>Preset resolutions</b>	VGA: 640x350, 640x480, 720x400 SVGA: 800x600 XGA: 1024x768, 1152x864 SXGA: 1280x1024 WXGA: 1280x768, 1280x800, 1366x768 WXGA+: 1440x900 UXGA: 1600x1200 WSXGA+: 1680x1050 Full HD: 1920x1080 WUXGA: 1920x1200	<b>ThinkVision LT2452p Wide Monitor</b>
<b>Presets / user settings</b>	Standard presets: 30; user settings: 20	
<b>Viewing adjustments</b> <b>Rotating screen</b> <b>On screen display</b> <b>Control features</b> <b>USB hub</b> <b>Multiple input</b> <b>Monitor connectors</b>	<i>Tilt: 30° back, 0° forward; lift: 4.3" (110mm); swivel: +/-45°; detachable stand</i> <b>Screen pivots 90 degrees from landscape to portrait</b> (requires image rotation support from graphics controller) On screen display with digital user controls (8 languages) Direct access (buttons on front) for automatic image setup, input switch, and brightness USB 2.0 Hub (1 port into PC, 4 ports for accessories) Triple input (three different PCs attach to three different connectors; one PC shows image; select via button) (1) VGA 15-pin D-shell, analog, blue (2) DisplayPort, digital, black, <b>HDCP-compliant</b> (3) Digital Visual Interface (DVI-D), digital, white, <b>HDCP-compliant</b>	
<b>Signal cables</b>	(1) detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter (2) detachable, DVI-D at each end, digital, 1.8 meter Note: DisplayPort cable is not included; use optional DisplayPort to DisplayPort Monitor Cable (0A36537)	
<b>Mounting features</b> <b>Security</b>	Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPI® (100mm mount) Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)	
<b>Ship group</b>	Monitor, attached stand, cable cover, Setup poster, Safety and Warranty Information, CD with multilingual User's Guide and monitor installation files, 1.8 meter analog signal cable, 1.8 meter DVI-D cable, 1.8 meter USB cable, 1.8 meter black power cord	

<b>Limited Warranty</b> <ul style="list-style-type: none"> <li>⇒ <b>3 year limited warranty<sup>4</sup></b></li> <li>⇒ <b>International Warranty Service<sup>5</sup></b></li> <li>⇒ <b>Rapid Replacement Service at 1-800-426-7378</b></li> <li>⇒ <b>Replacement normally arrives in two business days, excluding holidays</b></li> <li>⇒ <b>Lenovo pays all shipping costs for valid warranty claims<sup>6</sup></b></li> <li>⇒ <b>Service upgrade options:<sup>7</sup></b> <ul style="list-style-type: none"> <li>• <b>3 year, on site exchange, Mon-Fri 9-5 with next day response</b> (ThinkPlus™ part number 41C9209)</li> <li>• <b>3 year, on site exchange, 7 day x 24 hr with 4 hour response</b> (41C9212)</li> <li>• <b>4 year, on site exchange, Mon-Fri 9-5 with next day response</b> (41C9233)</li> <li>• <b>4 year, on site exchange, 7 day x 24 hr with 4 hour response</b> (41C9216)</li> <li>• <b>4 year, mail exchange</b> (51J0589)</li> <li>• <b>5 year, mail exchange</b> (51J0590)</li> </ul> </li> <li>⇒ <b>24x7<sup>8</sup> day toll-free support for warranty issues during the warranty period<sup>4</sup></b></li> </ul>	<b>Accessories</b> <table> <tr> <td>DisplayPort to DisplayPort Monitor Cable</td><td>0A36537</td></tr> <tr> <td>ThinkVision Soundbar</td><td>45K1263</td></tr> <tr> <td>Kensington MicroSaver Cable Lock</td><td>73P2582</td></tr> <tr> <td>Kensington Twin Head Cable Lock</td><td>45K1620</td></tr> <tr> <td>Lenovo Security Cable Lock</td><td>57Y4303</td></tr> <tr> <td>ThinkCentre Extend Arm</td><td>57Y4352</td></tr> <tr> <td>Lenovo Easy Reach Monitor Stand</td><td>55Y9258</td></tr> </table> <p>See details at <a href="http://www.lenovo.com/support/monitoraccessories">www.lenovo.com/support/monitoraccessories</a></p> <p>See all monitors at <a href="http://www.lenovo.com/thinkvision">www.lenovo.com/thinkvision</a></p>	DisplayPort to DisplayPort Monitor Cable	0A36537	ThinkVision Soundbar	45K1263	Kensington MicroSaver Cable Lock	73P2582	Kensington Twin Head Cable Lock	45K1620	Lenovo Security Cable Lock	57Y4303	ThinkCentre Extend Arm	57Y4352	Lenovo Easy Reach Monitor Stand	55Y9258
DisplayPort to DisplayPort Monitor Cable	0A36537														
ThinkVision Soundbar	45K1263														
Kensington MicroSaver Cable Lock	73P2582														
Kensington Twin Head Cable Lock	45K1620														
Lenovo Security Cable Lock	57Y4303														
ThinkCentre Extend Arm	57Y4352														
Lenovo Easy Reach Monitor Stand	55Y9258														





ThinkVision® USB Soundbar  
(40Y7616)



ThinkVision Soundbar  
(45K1263)



Kensington® MicroSaver® Cable Lock from Lenovo  
(73P2582)

Kensington Twin Head Cable Lock from Lenovo  
(45K1620)

Lenovo Security Cable Lock  
(57Y4303)



Lenovo Easy Reach Monitor Stand  
(55Y9258)



ThinkCentre Extend Arm  
(57Y4352)





Lenovo USB-to-DVI Monitor Adapter  
(45K5296)



Lenovo DisplayPort to VGA Monitor Cable  
(57Y4393)

Lenovo DisplayPort to Single-link DVI-D Monitor Cable  
(45J7915)

Lenovo Mini-DisplayPort to VGA Monitor Cable  
(0A36536)

Lenovo DisplayPort to DisplayPort Monitor Cable  
(0A36537)

**Monitor Accessories<sup>46</sup>** (all part numbers listed are US option P/N)

 Lenovo USB-to-DVI Monitor Adapter \*\* 45K5296 *ann 05/12/09*

 Lenovo DisplayPort to VGA Monitor Cable \*\* 57Y4393 *ann 08/04/09*

 DisplayPort to Single-link DVI-D Cable \*\* 45J7915 *ann 08/05/08*

 Lenovo Mini-DisplayPort to VGA Monitor Cable \*\* 0A36536 *ann 05/17/11*

\*\* Supports a maximum 1920 x 1200 monitor resolution.

 Lenovo DisplayPort to DisplayPort Monitor Cable\*\*\* 0A36537 *ann 09/13/11*

\*\*\*Hardware requirement: All Lenovo systems and monitors with DisplayPort 1.1a or 1.2 interface.

ThinkVision® USB Soundbar

 40Y7616 *ann 08/23/05*

ThinkVision Soundbar

 45K1263 *ann 09/16/08*

Kensington® MicroSaver® Cable Lock

 73P2582 *ann 12/29/03*

Kensington Twin Head Cable Lock

 45K1620 *ann 09/30/08*

Lenovo Security Cable Lock

 57Y4303 *ann 08/24/10*

Lenovo Easy Reach Monitor Stand

 55Y9258 *ann 09/22/09*

ThinkCentre Extend Arm

 57Y4352 *ann 07/06/10*
<sup>46</sup> Compatible on selected Lenovo and ThinkVision monitors.

**Compatibility matrix**

	USB-to-DVI Adapter (45K5296)	DisplayPort to VGA Cable (57Y4393)	DisplayPort to DVI-D Cable (45J7915)	Mini-DisplayPort to VGA Monitor Cable (0A36536)	ThinkVision USB Soundbar (40Y7616)	ThinkVision Soundbar (45K1263)	MicroSaver Cable Lock (73P2582)	Twin Head Cable Lock (45K1620)	Security Cable Lock (57Y4303)	Easy Reach Monitor Stand (55Y9258)	Extend Arm (57Y4352)
LT1421							X	X	X		
L1711p	x*	x	x	x		x	x	x	x	x	x
D186		x		x			x	x	x	x	x
L197	x	x	x	x	x		x	x	x	x	x
L1900p	x	x	x	x		x	x	x	x	x	x
L1951p	x	x	x	x		x	x	x	x	x	x
LT1952p	x	x	x	x		x	x	x	x	x	x
L2021	x	x	x	x		x	x	x	x	x	x
LS2221				x			x	x	x	x	x
L2250p	x	x	x	x		x	x	x	x	x	x
L2251p	x	x		x		x	x	x	x	x	x
LT2252p	x	x	x	x		x	x	x	x	x	x
L2251x	x	x		x		x	x	x	x	x	x
L2321x	x	x		x		x	x	x	x	x	x
LS2421p				x			x	x	x	x	x
L2440p	x	x	x	x		x	x	x	x	x	x
LT2452p	x	x	x	x		x	x	x	x	x	x
L2461x		x		x			x	x	x	x	x
<i>End of marketing</i>											
< L151	x	x			x		x	x		x	
< L151p	x	x	x		x		x	x		x	
< L171	x	x			x		x	x		x	
< L171p	x	x	x		x		x	x		x	
< L172	x	x			x		x	x		x	
< L174	x	x	x		x		x	x		x	
< L1700p	x	x	x		x		x	x		x	
< D185	x	x	x			x	x	x		x	
< L190x	x	x	x		x		x	x		x	
< L191	x	x			x		x	x		x	
< L192p	x	x	x		x		x	x		x	
< L193p	x	x	x		x		x	x		x	
< L194	x	x	x		x		x	x		x	
< L1940p	x	x	x		x		x	x		x	
< L200p	x	x	x		x		x	x		x	
< L201p	x	x	x		x		x	x		x	
< L2060	x	x	x				x	x	x	x	x
< L215	x	x	x			x	x	x		x	
< L215p	x	x			x		x	x		x	
< L220x	x	x			x		x	x		x	
< L2230x	x	x				x	x	x	x	x	x
< L2240p	x	x	x		x		x	x		x	
< L2440x	x	x	x			x	x	x		x	

\* Character "x": option supported on monitor

 More information at [www.lenovo.com/support/monitoraccessories](http://www.lenovo.com/support/monitoraccessories)

 Other accessories at [www.lenovo.com/accessories](http://www.lenovo.com/accessories)

 Accessories Guide pdf at [www.lenovo.com/accessoriesguide](http://www.lenovo.com/accessoriesguide)

**Availability:** All offers subject to availability. Lenovo reserves the right to alter product offerings and specifications at any time, without notice. Lenovo is not responsible for photographic or typographic errors.

**Warranty:** For a copy of applicable product warranties, write to: Warranty Information, P.O. Box 12195, RTP, NC, 27709, Attn: Dept ZPYA/B676. Lenovo makes no representation or warranty regarding third party products or services.

<sup>1</sup> **ISO-compliant:** Compliance with ISO 9241 Part 3, ISO Part 7, ISO Part 8, and/or ISO 13406 Part 2 is dependent on a complete ISO-capable platform of a system unit, monitor, video subsystem, operating system and fonts.

<sup>2</sup> **VESA:** Requires attachment to suitably configured system with similarly enabled operating system.

<sup>3</sup> **ENERGY STAR:** As an ENERGY STAR partner, Lenovo has determined that this product meets the ENERGY STAR 4.0 or 4.1 guidelines for energy efficiency. Requires attachment to suitably configured system.

<sup>4</sup> **Limited warranty:** Support unrelated to a warranty issue may be subject to additional charges.

<sup>5</sup> **International Warranty Service** is available in any country in which this product is sold and serviced. Service delivery methods and parts availability vary by country, may be different from that in the country of purchase, and are subject to change without notice. Fees and restrictions may apply in some countries.

<sup>6</sup> **Lenovo pays all shipping costs** for warranty repairs during limited warranty period.

<sup>7</sup> **ThinkPlus and Lenovo Care Services:** These services are available for machines normally used for business, professional, or trade purposes, rather than personal, family, or household purposes. Not all machine types and models are covered. Service period begins with the equipment date of purchase. Service must be purchased during the original limited product warranty period. Service levels are response time objectives and are not guarantees. If the machine problem turns out to be a Customer Replaceable Unit (CRU), a part will be express shipped to you for quick replacement. Onsite 24x7x2-hour service is not available in all locations. P&L means parts and labor. P/U means pick-up. See terms and conditions for complete details and restrictions.

<sup>8</sup> **Telephone support** may be subject to additional charges, even during the limited warranty period. In the United States call 1-800-426-7378. Response times may vary. May exclude some holidays. If a machine is listed as having "On-site service for select repairs", this means that onsite service is available only for the replacement of select parts. For all other warranty repairs, Lenovo will provide the customer a replacement part for customer installation. The parts for which onsite service is available varies by machine, but may include the processor, power supply, heat sink, system board, or base cover. For machines with EasyServ or Courier service, Lenovo will attempt to diagnose and resolve the problem remotely before sending a courier.

<sup>10</sup> **TAA:** Monitor is compliant with the U.S. Federal Government's country-of-origin requirements prescribed in 48 C.F.R. Subpart 25.4; Trade Act Agreement (TAA) model.

<sup>11</sup> **Post-warranty annual maintenance agreement:** Service begins at the end of the base warranty or the end of any other applied warranty and maintenance option, whichever occurs last. Service delivery is not available the same day the maintenance agreement is purchased. Maintenance agreements must be purchased and the registration successfully completed prior to the service being available.

<sup>12</sup> **Halogen:** Less than 900 Parts Per Million. Low halogen is defined in accordance with IPC-401B and draft IPC-J-STD 709 Class 1 requirements.



**Trademarks:** Lenovo, the Lenovo logo, New World. New Thinking., Access Connections, Rescue and Recovery, ThinkCentre, ThinkPad, ThinkStation, ThinkVantage, and ThinkVision are trademarks of Lenovo. Microsoft, Windows, and Vista are registered trademarks of Microsoft Corporation. Other company, product, or service names may be trademarks or service marks of others.

This publication was developed for products and services offered in the United States. Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to alter specifications and other product information at any time without prior notice. Lenovo is not responsible for photographic or typographical errors. **LENOVO PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions; therefore this disclaimer may not apply to you. This publication was developed in the US.

Visit [www.lenovo.com/safecomputing](http://www.lenovo.com/safecomputing) periodically for the latest information on safe and effective computing.

Visit [www.lenovo.com/psref](http://www.lenovo.com/psref) for the latest version of Personal Systems Reference.

© Lenovo, 2011.  
All rights reserved.

Lenovo  
1009 Think Place  
Morrisville, NC 27560  
U.S.A.

September 2011  
mbook.pdf